

CONTACT US! 1-800-249-1612 rtautomation.com

Real Time Automation Gateways

460BCDFM-N700

Connect BACnet/IP Devices to Legacy DF1 PLCs

FEATURES

- Fully configurable BACnet/IP client
- BACnet/IP supports device, binary I/O/V, analog I/O/V, multistate I/O/V, and character string value object types
- Support for PLC5, SLC and MicroLogix PLCs
- Connect up to 32 DF1 serial devices
- Effortless Browser Based Configuration, no programming software is required
- Simple data translation allows you to manipulate data as it passes between protocols
- Guaranteed Stock
- 5-Year Hardware Warranty

Control up to 32 BACnet/IP Server Devices from a Serial PLC5, SLC, or MicroLogix PLC

You can now control a network of 32 BACnet/IP server devices from a legacy Allen-Bradley serial PLC. It's the perfect tool to save legacy PLCs from the scrap pile.

You can now extend the function of the legacy PLCs you already have.

How Do I Use the 460BCDFM-N700 in My Application?

For most applications the mapping is very straightforward. PLC data table values like N7:200 and F9:1 are mapped directly to BACnet analog and binary values.

It really is that simple.

Why Use Real Time Automation as a Gateway Supplier?

While there are certainly other companies offering protocol gateways, there is no one who provides the level of support and service that you receive from RTA.

When you call, a live person answers the phone. When you talk with sales, you will get honest answers and recommendations. When you get support, it is from an engineer who had a hand in the product's development, and support doesn't require a ticket or 24-hour wait.



A Solution, A Philosophy, the RTA Way. We understand the long hours spent on a factory floor and the pressure to keep a line running and product flowing. That's how Real Time Automation came to be. You want easy-to-use solutions where the hardest part is to open the box. You need customer support second to none. If you get all that and a fun customer experience all the better. Thirty years later, our mission remains the same: To move your data where you need it, when you need it, and how you need it.

Specification

| BACnet/IP Client | | |
|---|---|--|
| Operation Mode | BACnet/IP Client | |
| Supported Object Types | Device, BI/BO/BV, AI/AO/AV, MI/MO/MV, Character String Value | |
| Supported Service Codes | Read Property-A, Read Property Multiple-A, Write Property-A, Write Property Multiple-A, Device Dynamic Binding-A | |
| Maximum Connections | 32 | |
| Number Read/Write Scan Lines per Device | 200 Total - 100 reads & 100 writes | |
| Scan Line Support | Up to 128 Objects | |
| DF1 Master | | |
| Operation Mode | DF1 Master Full Duplex and DF1 Master Half Duplex | |
| PLCs Supported | MicroLogix 1000, SLC 5/03 5/04 5/05, most PLC5s | |
| Maximum number of Devices supported | 1 in Full Duplex Mode, 32 in Half Duplex | |
| Data Type Supported | 100 Integers or 100 Binaries, or 50 floats, 82 character string per Scan line | |
| Scan Lines | 100 input / 100 output | |
| Physical Connections | RS-485 and RS-232 | |
| INCLUDED WITH GATEWAY | | |
| 3' power cable with flying leads | 5-year hardware warranty | |
| IPSetup software – automatically locates RTA gateway on the network | Unlimited firmware feature upgrades for life | |
| CAT5 crossover cable for direct connection to PC during programming | Complete, unlimited access to our industry leading support staff | |
| Optional: Generic 1761-CBL-PM02 Cable | Optional: NULL Modem Cable | |

ELECTRICAL / ENVIRONMENTAL

| ELECTRICAL / ENVIRONMENTAL | | |
|---------------------------------------|---|---|
| DC Input Voltage | 12-24 VDC | |
| Maximum Baud Rate | 115K baud | |
| Operating Temperature | -40 C to 85 C | |
| Certification | RoHS-Compliant, UL, CUL, CE Approvals | |
| ENCLOSURE / HARDWARE | | Ithernet d |
| Size | 4.19" x 3.25" x 1" | p i |
| Weight | 6.5 oz | 3,26 |
| Enclosure Type | Anodized Aluminum | |
| Mounting | Din rail or panel mount | Note: All dimension |
| LEDs | Power LED, Ethernet link/data LED, & Ethernet speed LED | |
| GATEWAY FEATURES & FUNCTIO | ONS | - 100 |
| Alarming | Set <, <=, >, >=, ==, !=, and change-of-state rules on any data moving through the gateway. If alarm rule is triggered an email notification can be sent. | Din Rail |
| Gateway Security | You can configure up to 9 different users access to diagnostic and configuration screens. | Panel Mount |
| Translation Table | Allows for data manipulation during protocol translation. Scaling and other data format changes can occur in the gateway. | |
| Status and Counters | Protocol specific status, counters, and error messages are accessible within the gateway's diagnostics page. They can also be delivered to a connected device. | NOT EXACTLY WHAT YOU WERE LOOKING FOR? Real Time Automation offers a full line of gateway products. Give us a call at 1-800-249-1612. Or, check out a listing at www.rtautomation.com/products. We also offer customizations for unique applications. |
| Diagnostic Logging Page | Allows users to see and log start up sequences, protocol specific messages & error messages. | |

| CATALOG # | DESCRIPTION |
|---------------|---|
| 460BCDFM-N700 | Connects up to 32 BACnet/IP servers with as many as 32 DF1 slaves |













Real Time Automation, Inc.

solutions@rtautomation.com

1-800-249-1612