CONTACT US!

1-800-249-1612 rtautomation.com

Real Time Automation Gateways

460BMSDFM-N700

Get Your Serial DF1 PLC Data into a BACnet MS/TP Network

FEATURES

- Fully configurable BACnet MS/TP responder
- BACnet MS/TP supports device, binary I/O, analog I/O, and character string value object types
- Support for PLC5, SLC and MicroLogix PLCs
- Connect up to 32 DF1 serial devices
- Effortless Browser
 Based Configuration,
 no programming
 software is required
- Simple data translation allows you to manipulate data as it passes between protocols
- Guaranteed Stock
- 5-Year Hardware Warranty

Map Your Legacy PLC Data Tables into a BACnet MS/TP Master

You can now make your legacy serial PLCs look like a BACnet MS/TP device! Any of your old serial PLCs like the PLC5, SLC, or MicroLogix cannot provide data to a BACnet MS/TP building automation system.

It's the perfect tool to keep those old legacy PLCs from the scrap pile.

How Do I Use the 460BMSDFM-N700 in My Application?

For most applications, the mapping is very straightforward. PLC data table values like N7:200 and F9:1 are mapped directly to BACnet analog and binary values.

No message instructions and no ladder logic changes are required to monitor the PLC data on BACnet MS/TP.

Why Use Real Time Automation as a Gateway Supplier?

While there are certainly other companies offering protocol gateways, there is no one who provides the level of support and service that you receive from RTA.

When you call, a live person answers the phone. When you talk with sales, you will get honest answers and recommendations. When you get support, it is from an engineer who had a hand in the product's development, and support doesn't require a ticket or 24-hour wait.



A Solution, A Philosophy, the RTA Way. We understand the long hours spent on a factory floor and the pressure to keep a line running and product flowing. That's how Real Time Automation came to be. You want easy-to-use solutions where the hardest part is to open the box. You need customer support second to none. If you get all that and a fun customer experience all the better. Thirty years later, our mission remains the same: To move your data where you need it, when you need it, and how you need it.

Specification

BACnet MS/TP Slave		
Operation Mode	BACnet MS/TP Master Responder	
Supported Object Types	Device, Binary I/O, Analog I/O, Character String Value	
Supported Service Codes	Read & Read Multiple-B, Write & Write Multiple-B, COV & COV unsolicited-B, Device Dynamic Binding-B, Dynamic Object Binding-B	
Maximum Connections	1	
Analog Objects Supported	1200 Input and 1200 Output	
Binary Objects Supported	1600 Input and 1600 Output	
DF1 Master		
Operation Mode	DF1 Master Full Duplex and DF1 Master Half Duplex	
PLCs Supported	MicroLogix 1000, SLC 5/03 5/04 5/05, most PLC5s	
Maximum number of Devices supported	1 in Full Duplex Mode, 32 in Half Duplex	
Data Type Supported	100 Integers or 100 Binaries, or 50 floats, 82 character string per Scan line	
Scan Lines	100 input / 100 output	
Physical Connections	RS-485 and RS-232	
INCLUDED WITH GATEWAY		
3' power cable with flying leads	5-year hardware warranty	
IPSetup software – automatically locates RTA gateway on the network	Unlimited firmware feature upgrades for life	
CAT5 crossover cable for direct connection to PC during programming	Complete, unlimited access to our industry leading support staff	
Optional: Generic 1761-CBL-PM02 Cable	Optional: NULL Modem Cable	

ELECTRICAL / ENVIRONMENTAL		
DC Input Voltage	12-24 VDC	
Maximum Baud Rate	115K baud	
Operating Temperature	-40 C to 85 C	b (8)
Certification	RoHS-Compliant, UL, CUL, CE Approvals	
ENCLOSURE / HARDWARE		Ithernet 0
Size	4.19" x 3.25" x 1"	
Weight	6.5 oz	3,25
Enclosure Type	Anodized Aluminum	
Mounting	Din rail or panel mount	Note: All dimension
LEDs	Power LED, Ethernet link/data LED, & Ethernet speed LED	are ninches
GATEWAY FEATURES & FUNCTIONS		
Alarming	Set <, <=, >, >=, ==, !=, and change-of-state rules on any data moving through the gateway. If alarm rule is triggered an email notification can be sent.	Din Rail
Gateway Security	You can configure up to 9 different users access to diagnostic and configuration screens.	Panel Mount
Translation Table	Allows for data manipulation during protocol translation. Scaling and other data format changes can occur in the gateway.	••••
Status and Counters	Protocol specific status, counters, and error messages are accessible within the gateway's diagnostics page. They can also be delivered to a connected device.	NOT EXACTLY WHAT YOU WERE LOOKING FOR? Real Time Automation offers a full line of gateway products. Give us a call at 1-800-249-1612. Or, check out a listing at www.rtautomation.com/products . We also offer customizations for unique applications.
Diagnostic Logging Page	Allows users to see and log start up sequences, protocol specific messages & error messages.	

CATALOG #	DESCRIPTION
460BMSDFM-N700	Connects a BACnet MS/TP master with as many as 32 DF1 slaves



Made in the

U.S.A.



Always In





