CONTACT US!

1-800-249-1612 rtautomation.com

Real Time Automation Gateways

460BMSTCP-N700

Ethernet TCP/IP to BACnet MS/TP

FEATURES

- Fully configurable BACnet MS/TP responder
- BACnet MS/TP supports device, binary I/O, analog I/O, and character string value object types
- Support up to 10 TCP/IP devices
- Parse & concatenate ASCII data in up to 50 segments by delimiter or offset
- Effortless Browser
 Based Configuration,
 no programming
 software is required
- Simple data translation allows you to manipulate data as it passes between protocols
- Guaranteed Stock
- 5-Year Hardware Warranty

Get Ethernet TCP/IP Data into your BACnet MS/TP Network

The 460BMSTCP moves data between up to 10 Ethernet TCP/IP devices and a BACnet MS/TP Building Automation System (BAS). It's the perfect tool to tie Ethernet TCP/IP devices into your BACnet MS/TP building automation system.

A great tool to connect printers, RFID devices, LED displays, and PC applications to a BACnet MS/TP system.

How Do I Use the 460BMSTCP-N700 in My Application?


BACnet analog, binary, and CSV data segments can be converted to ASCII and delivered to your ASCII controller. If you need to command the BACnet/IP servers, an incoming ASCII string can be parsed and directed to user-defined data location.

It really is that simple.

Why Use Real Time Automation as a Gateway Supplier?

While there are certainly other companies offering protocol gateways, there is no one who provides the level of support and service that you receive from RTA.

When you call, a live person answers the phone. When you talk with sales, you will get honest answers and recommendations. When you get support, it is from an engineer who had a hand in the product's development, and support doesn't require a ticket or 24-hour wait.



A Solution, A Philosophy, the RTA Way. We understand the long hours spent on a factory floor and the pressure to keep a line running and product flowing. That's how Real Time Automation came to be. You want easy-to-use solutions where the hardest part is to open the box. You need customer support second to none. If you get all that and a fun customer experience all the better. Thirty years later, our mission remains the same: To move your data where you need it, when you need it, and how you need it.

Specification

BACnet MS/TP Slave	
Operation Mode	BACnet MS/TP Master Responder
Supported Object Types	Device, Binary I/O, Analog I/O, Character String Value
Supported Service Codes	Read & Read Multiple-B, Write & Write Multiple-B, COV & COV unsolicited-B, Device Dynamic Binding-B, Dynamic Object Binding-B
Maximum Connections	1
Analog Objects Supported	1200 Input and 1200 Output
Binary Objects Supported	1600 Input and 1600 Output
Ethernet TCP/IP	
Operation Mode	Client or Server
Maximum Number of Devices Supported	10
Maximum Number of Characters Transferred	1024
Delimiter Processing	Incoming delimiters can be automatically removed; Outgoing delimiters automatically added if configured
Parsing	Parse String of ASCII Data in up to 50 Segments by Delimiter or Offset
Concatenation	Concatenate up to 50 segments/strings of ASCII data with optional delimiter
INCLUDED WITH GATEWAY	
3' power cable with flying leads	5-year hardware warranty
IPSetup software – automatically locates RTA gateway on the network	Unlimited firmware feature upgrades for life
CAT5 crossover cable for direct connection to PC during programming	Complete, unlimited access to our industry leading support staff
Manual	

12-24 VDC 115K baud -40 C to 85 C RoHS-Compliant, UL, CUL, CE Approvals 4.19" x 3.25" x 1" 6.5 oz Anodized Aluminum	Internet	Poet 1
-40 C to 85 C RoHS-Compliant, UL, CUL, CE Approvals 4.19" x 3.25" x 1" 6.5 oz		Poet 1
RoHS-Compliant, UL, CUL, CE Approvals 4.19" x 3.25" x 1" 6.5 oz		Port 1
4.19" x 3.25" x 1" 6.5 oz		Port 1
6.5 oz		
6.5 oz	3.25	5 8
	3,25	
Anodized Aluminum		
		2 2
Din rail or panel mount	Note: All dimension	0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0
Power LED, Ethernet link/data LED, & Ethernet speed LED	are n inches	
GATEWAY FEATURES & FUNCTIONS		100
Set <, <=, >, >=, ==, !=, and change-of-state rules	1.0	- 1.00
on any data moving through the gateway. If alarm rule is triggered an email notification can be sent.	Din Rail	
You can configure up to 9 different users access to diagnostic and configuration screens.	Panel Mount	<u> </u>
Allows for data manipulation during protocol translation. Scaling and other data format changes can occur in the gateway.	•••	
Protocol specific status, counters, and error messages are accessible within the gateway's diagnostics page. They can also be delivered to a connected device.	Real Time Automation offers a full Give us a call at 1-800-249-1612. www.rtautomation.com/prod	line of gateway products Or, check out a listing a ucts. We also offer
Allows users to see and log start up sequences, protocol specific messages & error messages.		NAME:
	Power LED, Ethernet link/data LED, & Ethernet speed LED ONS Set <, <=, >, >=, ==, !=, and change-of-state rules on any data moving through the gateway. If alarm rule is triggered an email notification can be sent. You can configure up to 9 different users access to diagnostic and configuration screens. Allows for data manipulation during protocol translation. Scaling and other data format changes can occur in the gateway. Protocol specific status, counters, and error messages are accessible within the gateway's diagnostics page. They can also be delivered to a connected device. Allows users to see and log start up sequences,	Power LED, Ethernet link/data LED, & Ethernet speed LED ONS Set <, <=, >, >=, ==, !=, and change-of-state rules on any data moving through the gateway. If alarm rule is triggered an email notification can be sent. You can configure up to 9 different users access to diagnostic and configuration screens. Allows for data manipulation during protocol translation. Scaling and other data format changes can occur in the gateway. Protocol specific status, counters, and error messages are accessible within the gateway's diagnostics page. They can also be delivered to a connected device. NOT EXACTLY WHAT YOU WI Real Time Automation offers a full Give us a call at 1-800-249-1612. www.rtautomation.com/prod customizations for unique.

CATALOG #	DESCRIPTION
460BMSTCP-N700	Connects a BACnet MS/TP master with up to 10 Ethernet TCP/IP devices



Made in the

U.S.A.



Always In







