## CONTACT US!

1-800-249-1612 rtautomation.com

# **Real Time Automation Gateways**

## 460BMSWI-N2EW

## Web Interface to BACnet MS/TP Master

#### **FEATURES**

- Fully configurable BACnet MS/TP responder
- BACnet MS/TP supports device, binary I/O, analog I/O, and character string value object types
- Get PLC data table entries encoded in either JSON or XML
- Bidirectional data transfer supports both HTTP GET and POST
- Effortless Browser
   Based Configuration,
   no programming
   software is required
- Simple data translation allows you to manipulate data as it passes between protocols
- Guaranteed Stock
- 5-Year Hardware Warranty

#### Access your BACnet MS/TP Building Management System from a Web Client

With the 460BMSWI, it is easier than ever to monitor your BACnet MS/TP control system data via a web applications. Use that data to easily build dashboard, archive data, or create a sophisticated alarm system. The gateway presents the data as JSON or XML files transferred via HTTP commands.

Best of all, the product is made in the USA, always in stock, and comes with 5-year warranty.

#### How Do I Use the 460BMSWI-N2EW in My Application?

First, you configure the 460BMSWI using the browser-based configuration pages. You'll identify the data set to expose on BACnet. This will identify the BACnet analog and binary points that will be available for you to read/write. Once that's complete, you'll map, name, and group the data to be presented as XML or JSON files.

Your application can issue standard HTTP GET or POST instructions to move data into your application. Up to 1000 data points can be moved.

#### Why Use Real Time Automation as a Gateway Supplier?

While there are certainly other companies offering protocol gateways, there is no one who provides the level of support and service that you receive from RTA.

When you call, a live person answers the phone. When you talk with sales, you will get honest answers and recommendations. When you get support, it is from an engineer who had a hand in the product's development, and support doesn't require a ticket or 24-hour wait.



A Solution, A Philosophy, the RTA Way. We understand the long hours spent on a factory floor and the pressure to keep a line running and product flowing. That's how Real Time Automation came to be. You want easy-to-use solutions where the hardest part is to open the box. You need customer support second to none. If you get all that and a fun customer experience all the better. Thirty years later, our mission remains the same: To move your data where you need it, when you need it, and how you need it.

# **Specification**

BACnet MS/TP Slave			
Operation Mode	BACnet MS/TP Master Responder		
Supported Object Types	Device, Binary I/O, Analog I/O, Character String Value		
Supported Service Codes	Read & Read Multiple-B, Write & Write Multiple-B, COV & COV unsolicited-B, Device Dynamic Binding-B, Dynamic Object Binding-B		
Maximum Connections	1		
Analog Objects Supported	1200 Input and 1200 Output		
Binary Objects Supported	1600 Input and 1600 Output		
Web Interface			
Max Web Interface Connections	One (gateway acting as client) / Unlimited (gateway acting as server)		
Encodings	JSON and XML		
Proxy Support	HTTP, SOCKS5 for Client		
Maximum Number of Input Data Points	1000 JSON Fields or 1000 XML Tags		
Maximum Number of Output Data Points	1000 JSON Fields or 1000 XML Tags		
HTTP Services	Client: POST only; Server: GET and POST		
INCLUDED WITH GATEWAY			
3' power cable with flying leads	5-year hardware warranty		
IPSetup software – automatically locates RTA gateway on the network	Unlimited firmware feature upgrades for life		
CAT5 crossover cable for direct connection to PC during programming	Complete, unlimited access to our industry leading support staff		
Manual			

<b>ELECTRICAL / ENVIRONMENT</b>	AL	
DC Input Voltage	12-24 VDC	
Maximum Baud Rate	115K baud	
Operating Temperature	-40 C to 85 C	
Certification	RoHS-Compliant, UL, CUL, CE Approvals, Class I Div 2	3.83
ENCLOSURE / HARDWARE		
Size	5.40" x 3.83" x 1.19"	
Weight	7.6 oz	
Enclosure Type	Anodized Aluminum	
Mounting	Din rail or panel mount	
LEDs	Power LED & 2 general purpose LEDs on side	<del> </del>   ≒
<b>GATEWAY FEATURES &amp; FUNC</b>	CTIONS	
Alarming	Set <, <=, >, >=, ==, !=, and change-of-state rules on any data moving through the gateway. If alarm rule is triggered an email notification can be sent.	
Gateway Security	You can configure up to 9 different users access to diagnostic and configuration screens.	
Translation Table	Allows for data manipulation during protocol translation. Scaling and other data format changes can occur in the gateway.	
Status and Counters	Protocol specific status, counters, and error messages are accessible within the gateway's diagnostics page. They can also be delivered to a connected device.	NOT EXACTLY WHAT YOU WERE L Real Time Automation offers a full line of Give us a call at 1-800-249-1612. Or, ch www.rtautomation.com/products. V customizations for unique appl
Diagnostic Logging Page	Allows users to see and log start up sequences, protocol specific messages & error messages.	

- 5.40-		
NOT EXACTLY WHAT YOU WERE LOOKING FOR? Real Time Automation offers a full line of gateway products. Give us a call at 1-800-249-1612. Or, check out a listing at  www.rtautomation.com/products. We also offer customizations for unique applications.		

CATALOG #	DESCRIPTION
460BMSWI-N2EW	Access your BACnet MS/TP building management system from a web client



Made in the

U.S.A.



Always In

Stock





