

CONTACT US! 1-800-249-1612 rtautomation.com

### **Real Time Automation Gateways**

# 460BMWI-N700

### **Connect a Web Interface to BACnet MS/TP Slaves**

#### FEATURES

- Fully configurable BACnet MS/TP master
- BACnet MS/TP supports device, binary I/O/V, analog I/O/V, multi-state I/O/V, and character string value object types
- Get PLC data table entries encoded in either JSON or XML
- Bidirectional data transfer supports both HTTP GET and POST
- Effortless Browser Based Configuration, no programming software is required
- Simple data translation allows you to manipulate data as it passes between protocols
- Guaranteed Stock
- 5-Year Hardware Warranty

#### Deliver Data from Your BACnet MS/TP Slave Devices to a Web Interface

The 460BMWI moves data between up to 32 BACnet MS/TP slave devices and a web server or a web client. Use that data to easily build an Excel log, a dashboard, archive data, or create a sophisticated alarm system.

Best of all, the product is made in the USA, always in stock, and comes with a 5-year warranty.

#### How Do I Use the 460BMWI-N700 in My Application?


First, you configure the 460BMWI using the browser-based configuration pages. You'll identify the data set to read / write on BACnet. Once that's complete, you'll map, name, and group the data to be presented as XML or JSON files.

Your application can issue standard HTTP GET or POST instructions to move data into your application. Up to 1000 data points can be moved in each direction.

#### Why Use Real Time Automation as a Gateway Supplier?

While there are certainly other companies offering protocol gateways, there is no one who provides the level of support and service that you receive from RTA.

When you call, a live person answers the phone. When you talk with sales, you will get honest answers and recommendations. When you get support, it is from an engineer who had a hand in the product's development, and support doesn't require a ticket or 24-hour wait.



A Solution, A Philosophy, the RTA Way. We understand the long hours spent on a factory floor and the pressure to keep a line running and product flowing. That's how Real Time Automation came to be. You want easy-to-use solutions where the hardest part is to open the box. You need customer support second to none. If you get all that and a fun customer experience all the better. Thirty years later, our mission remains the same: To move your data where you need it, when you need it, and how you need it.

**ELECTRICAL / ENVIRONMENTAL** 

DC Input Voltage


## **Specification**

BACnet MS/TP Master	
Operation Mode	BACnet MS/TP Master Initiator
Supported Object Types	Device, BI/BO/BV, AI/AO/AV, MI/MO/MV, Character String Value
Supported Service Codes	Read Property-A, Read Property Multiple-A, Write Property-A, Write Property Multiple-A, Device Dynamic Binding-A
Maximum Connections	32
Number Read/Write Scan Lines per Device	200 Total - 100 reads & 100 writes
Scan Line Support	Up to 128 Objects
Web Interface	
Max Web Interface Connections	One (gateway acting as client) / Unlimited (gateway acting as server)
Encodings	JSON and XML
Proxy Support	HTTP, SOCKS5 for Client
Maximum Number of Input Data Points	1000 JSON Fields or 1000 XML Tags
Maximum Number of Output Data Points	1000 JSON Fields or 1000 XML Tags
HTTP Services	Client: POST only; Server: GET and POST
INCLUDED WITH GATEWAY	
3' power cable with flying leads	5-year hardware warranty
IPSetup software – automatically locates RTA gateway on the network	Unlimited firmware feature upgrades for life
CAT5 crossover cable for direct connection to PC during programming	Complete, unlimited access to our industry leading support staff
Manual	

#### 115K baud Maximum Baud Rate -40 C to 85 C **Operating Temperature** RoHS-Compliant, UL, CUL, CE Approvals Certification **ENCLOSURE / HARDWARE** Size 4.19" x 3.25" x 1" Weight 6.5 oz Enclosure Type Anodized Aluminum Din rail or panel mount Mounting Power LED, Ethernet link/data LED, & Ethernet LEDs speed LED **GATEWAY FEATURES & FUNCTIONS** Set <, <=, >, >=, ==, !=, and change-of-state rules Alarming on any data moving through the gateway. If alarm

12-24 VDC

Alaming	rule is triggered an email notification can be sent.
Gateway Security	You can configure up to 9 different users access to diagnostic and configuration screens.
Translation Table	Allows for data manipulation during protocol translation. Scaling and other data format changes can occur in the gateway.
Status and Counters	Protocol specific status, counters, and error messages are accessible within the gateway's diagnostics page. They can also be delivered to a connected device.
Diagnostic Logging Page	Allows users to see and log start up sequences, protocol specific messages & error messages.



NOT EXACTLY WHAT YOU WERE LOOKING FOR? Real Time Automation offers a full line of gateway products. Give us a call at 1-800-249-1612. Or, check out a listing at www.rtautomation.com/products. We also offer customizations for unique applications.

CATALOG #	DESCRIPTION
460BMWI-N700	Connects up to 32 BACnet MS/TP slave devices to a web interface













**Real Time Automation, Inc.** 

solutions@rtautomation.com

1-800-249-1612