

460DFMQT-NNA1

DF1 Slave to MQTT

FEATURES

- Support for PLC5, SLC and MicroLogix PLCs
- Connect up to 32 DF1 serial devices
- Bring your factory data to the cloud
- Support for MQTT, AWS and Azure
- Effortless Browser Based Configuration, no programming software is required
- Simple data translation allows you to manipulate data as it passes between protocols
- Guaranteed Stock
- 5-Year Hardware Warranty

Bridge DF1 Devices to MQTT

The 460TCPQT moves data between DF1 slaves and an MQTT application, AWS or Azure. Use the data to easily log data, build a dashboard or create a sophisticated alarm system.

Best of all, the product is made in the USA, always in stock, and comes with 5-year warranty.

How Do I Use the 460DFMQT-NNA1 in My Application?

Register data from your DF1 devices is mapped directly to topics in an MQTT broker.

SSL transport layer security protects the data moving from your operations network to the cloud.

Why Use Real Time Automation as a Gateway Supplier?

While there are certainly other companies offering protocol gateways, there is no one who provides the level of support and service that you receive from RTA.

When you call, a live person answers the phone. When you talk with sales, you will get honest answers and recommendations. When you get support, it is from an engineer who had a hand in the product's development, and support doesn't require a ticket or 24-hour wait.



A Solution, A Philosophy, the RTA Way. We understand the long hours spent on a factory floor and the pressure to keep a line running and product flowing. That's how Real Time Automation came to be. You want easy-to-use solutions where the hardest part is to open the box. You need customer support second to none. If you get all that and a fun customer experience all the better. Thirty years later, our mission remains the same: To move your data where you need it, when you need it, and how you need it.

Specification

DF1 Master	
Operation Mode	DF1 Master Full Duplex and DF1 Master Half Duplex
PLCs Supported	MicroLogix 1000, SLC 5/03 5/04 5/05, most PLC5s
Maximum number of Devices supported	1 in Full Duplex Mode, 32 in Half Duplex
Data Type Supported	100 Integers or 100 Binaries, or 50 floats, 82 character string per Scan line
Scan Lines	100 input / 100 output
Physical Connections	RS-485 and RS-232
MQTT	
Operation Mode	Generic MQTT, Amazon Web Services (AWS), Microsoft Azure
Max Broker Connections	Up to 3 Generic MQTT Connections, 1 AWS, 1 Azure
Max Data Points Per Connection	1000 Read and 1000 Write Topics
Security	SSL certificate based cloud access
Supported Data Formats	JSON
Data Payload	Topic Name and Value
INCLUDED WITH GATEWAY	
3' power cable with flying leads	5-year hardware warranty
IPSetup software – automatically locates RTA gateway on the network	Unlimited firmware feature upgrades for life
CAT5 crossover cable for direct connection to PC during programming	Complete, unlimited access to our industry leading support staff
Optional: Generic 1761-CBL-PM02 Cable	Optional: NULL Modem Cable

2-24 VDC 15K baud 0 C to 85 C DHS-Compliant, UL, CUL, CE Approvals 88" x 2.57" x 1.06" 5 oz nodized Aluminum in rail or panel mount ower LED & 2 general purpose LEDs on side <, <=, >, >=, ==, !=, and change-of-state rules	DIN Rail Mount	3.88
0 C to 85 C oHS-Compliant, UL, CUL, CE Approvals 88" x 2.57" x 1.06" 5 oz nodized Aluminum in rail or panel mount ower LED & 2 general purpose LEDs on side		
bHS-Compliant, UL, CUL, CE Approvals 88" x 2.57" x 1.06" 5 oz nodized Aluminum in rail or panel mount ower LED & 2 general purpose LEDs on side	2.57	3.88
88" x 2.57" x 1.06" 5 oz nodized Aluminum in rail or panel mount ower LED & 2 general purpose LEDs on side	2.57	3.88
5 oz nodized Aluminum in rail or panel mount ower LED & 2 general purpose LEDs on side	2.57	
5 oz nodized Aluminum in rail or panel mount ower LED & 2 general purpose LEDs on side	2.57	
nodized Aluminum in rail or panel mount ower LED & 2 general purpose LEDs on side	2.57	
n rail or panel mount ower LED & 2 general purpose LEDs on side	2.57	
ower LED & 2 general purpose LEDs on side	2.57	
and change of ctate rules		
> > - I and change of state rules	1.1	
any data moving through the gateway. If alarm is triggered an email notification can be sent.		Note: All dimensions are in Inches
u can configure up to 9 different users access to gnostic and configuration screens.		0000
ows for data manipulation during protocol islation. Scaling and other data format changes occur in the gateway.	1.06	0000
ssages are accessible within the gateway's gnostics page. They can also be delivered to a	Real Time Au Give us a cal www.rta	TLY WHAT YOU WERE L tomation offers a full line of l at 1-800-249-1612. Or, ch automation.com/products. \ tomizations for unique app
• • • • • • • • • • • • • • • • • • • •		
ו פר פר	n occur in the gateway. In occur in the gateway in occu	n occur in the gateway. NOT EXACT stocol specific status, counters, and error ssages are accessible within the gateway's gnostics page. They can also be delivered to a meeted device. NOT EXACT Real Time Aut Give us a call www.rte cus

7	3.88
2.57	lote: All dimensions
	are in Inches
1.06	
	TLY WHAT YOU WERE LOOKING FOR?
	omation offers a full line of gateway products at 1-800-249-1612. Or, check out a listing at
www.rta	utomation.com/products. We also offer omizations for unique applications.

CATALOG #	DESCRIPTION
460DFMQT-NNA1	Easily and securely connect DF1 slave data to cloud applications



Made in the



Always In

Stock





