# **CONTACT US!**

1-800-249-1612 rtautomation.com

# **Real Time Automation Gateways**

## 460DMSC-N34

### **Connect DeviceNet Slaves to Siemens S7 PLCs**

### **FEATURES**

- Fully configurable DeviceNet master
- Map data from up to 32 DeviceNet slaves
- Supports connections to five Siemens S7 PLCs
- Up to 150 read and 150 write requests per connection
- Effortless Browser Based Configuration, no programming software is required
- Simple data translation allows you to manipulate data as it passes between protocols
- **Guaranteed Stock**
- 5-Year Hardware Warranty

#### **Connect Siemens S7 PLCs to DeviceNet Slaves**

The 460DMSC moves data between one to five Siemens S7 PLCs and up to 32 DeviceNet slave devices.

Best of all, the product is made in the USA, always in stock, and comes with 5-year warranty.

### How Do I Use the 460DMSC-N34 in My Application?

For most applications, the mapping is very straightforward. Siemens S7 PLC data will be addressed in the PLC's I and Q addresses and can be mapped to up to 32 different DeviceNet slaves.

No message instructions and no ladder to alter in many cases.

#### Why Use Real Time Automation as a Gateway Supplier?

While there are certainly other companies offering protocol gateways, there is no one who provides the level of support and service that you receive from RTA.

When you call, a live person answers the phone. When you talk with sales, you will get honest answers and recommendations. When you get support, it is from an engineer who had a hand in the product's development, and support doesn't require a ticket or 24-hour wait.



A Solution, A Philosophy, the RTA Way. We understand the long hours spent on a factory floor and the pressure to keep a line running and product flowing. That's how Real Time Automation came to be. You want easy-to-use solutions where the hardest part is to open the box. You need customer support second to none. If you get all that and a fun customer experience all the better. Thirty years later, our mission remains the same: To move your data where you need it, when you need it, and how you need it.

DeviceNet Master		
Operation Mode	UCMM Client, Group 2 Client, Group 2 only Client	
Explicit Message Support	Yes, only for allocation process	
Implicit Message Support	Polled only, Assembly Object	
Maximum DeviceNet Slave Devices	32	
Data per Slave	0-400 Bytes in each direction	
Supported Data Types	BIT8, BIT16, BIT32, INT8, INT16, INT32, INT64, UINT8, UINT16, UINT32, UINT64, Float, Double	
S7 Client		
PLC Support	S7 300/400/1200/1500	
Maximum Number of PLCs Supported	5	
Maximum Number of Inputs/Outputs per PLC	150	
Maximum Number of Bytes per Scan Line	400	
Memory Area Access	Input (I), Output (Q), and Data Block( DB)	
Supported Data Types	8 Bit Int, 16 Bit Int, 32 Bit Int, 32 Bit Float, Bool and Char Array	
INCLUDED WITH GATEWAY		
3' power cable with flying leads	5-year hardware warranty	
IPSetup software – automatically locates RTA gateway on the network	Unlimited firmware feature upgrades for life	
CAT5 crossover cable for direct connection to PC during programming	Complete, unlimited access to our industry leading support staff	
Manual		

ELECTRICAL / ENVIRONMENTAL				
DC Input Voltage	8 VDC @ 230mA to 28 VDC @ 80 mA			
Maximum Baud Rate	115K baud			
Operating Temperature	-40 C to 85 C			
Certification	RoHS-Compliant, UL, CUL, CE Approvals, Class I Div 2			
ENCLOSURE / HARDWARE	NCLOSURE / HARDWARE			
Size	4.2" x 3.25" x 1"			
Weight	7 oz			
Enclosure Type	Anodized Aluminum			
Mounting	Din rail or panel mount			
LEDs	Ethernet link/data LED, Ethernet speed LED, power LED, & 2 general purpose LEDs on side			
GATEWAY FEATURES & FUNCTION	GATEWAY FEATURES & FUNCTIONS			
Alarming	Set <, <=, >, >=, ==, !=, and change-of-state rules on any data moving through the gateway. If alarm rule is triggered an email notification can be sent.			
Gateway Security	You can configure up to 9 different users access to diagnostic and configuration screens.			
Translation Table	Allows for data manipulation during protocol translation. Scaling and other data format changes can occur in the gateway.			
Status and Counters	Protocol specific status, counters, and error messages are accessible within the gateway's diagnostics page. They can also be delivered to a connected device.			
Diagnostic Logging Page	Allows users to see and log start up sequences, protocol specific messages & error messages.			

	LEOs	-h	
3.25		Port	0
		Ped 0	
1.00	4.19		1.00
Din Rail			
Panel Mount	<b>E-1</b>	=	
NOT EVACTIVE	WHAT YOU WERE I	OOKING	S FOR2

#### NOT EXACTLY WHAT YOU WERE LOOKING FOR? Real Time Automation offers a full line of gateway products. Give us a call at 1-800-249-1612. Or, check out a listing at www.rtautomation.com/products. We also offer

customizations for unique applications.

CATALOG #	DESCRIPTION
460DMSC-N34	Connects up to five Siemens S7 PLCs with as many as 32 DeviceNet slaves



Made in the



Always In







