CONTACT US!

1-800-249-1612 rtautomation.com

Real Time Automation Gateways

460ECBM-NNA4

EtherNet/IP to BACnet MS/TP Master with Wi-Fi

FEATURES

- Fully configurable EtherNet/IP scanner
- Map data from up to 32 EtherNet/IP adapters
- Fully configurable
 BACnet MS/TP master
- BACnet MS/TP supports device, binary I/O/V, analog I/O/V, multi-state I/O/V, and character string value object types
- Effortless Browser
 Based Configuration,
 no programming
 software is required
- Simple data translation allows you to manipulate data as it passes between protocols
- Guaranteed Stock
- 5-Year Hardware Warranty

Connect EtherNet/IP Adapter Devices to a BACnet MS/TP Master Wirelessly

The 460ECBMS moves data between a BACnet MS/TP master device and an EtherNet/IP network of up to 32 adapter devices. It's the perfect tool to tie in all of your EtherNet/IP devices into your BACnet MS/TP building automation system.

Bridge your factory automation systems with your building automation systems.

How Do I Use the 460ECBM-NNA4 in My Application?

Up to 496 of data from your EtherNet/IP adapters will be mapped into your BACnet MS/TP master. When writing from BACnet MS/TP to EtherNet/IP adapters up to 496 bytes of BACnet MS/TP data will be mapped to up to 32 EtherNet/IP adapters as EtherNet/IP data.

It's really that simple. Need to modify your data as it passes from one protocol to the other? No problem. Each data mapping you apply can be modified with up to three mathematic functions. Add 4 to a value, multiply by 4 and divide by 10 with ease.

Why Use Real Time Automation as a Gateway Supplier?

While there are certainly other companies offering protocol gateways, there is no one who provides the level of support and service that you receive from RTA.

When you call, a live person answers the phone. When you talk with sales, you will get honest answers and recommendations. When you get support, it is from an engineer who had a hand in the product's development, and support doesn't require a ticket or 24-hour wait.



A Solution, A Philosophy, the RTA Way. We understand the long hours spent on a factory floor and the pressure to keep a line running and product flowing. That's how Real Time Automation came to be. You want easy-to-use solutions where the hardest part is to open the box. You need customer support second to none. If you get all that and a fun customer experience all the better. Thirty years later, our mission remains the same: To move your data where you need it, when you need it, and how you need it.

Specification

EtherNet/IP Scanner		
Operation Mode	Class 1 I/O Scanner	
Message Support	Implicit Class 1 Cyclic I/O, Explicit not supported	
Data Types	BIT8,16 & 32; INT8, 16, 32 & 64; UINT8,16, 32 & 64; Float & Double	
Maximum EtherNet/IP Adapter Devices	32	
Max Data Per Adapter Connection	Up to 496 bytes in each direction	
Maximum IO Scan Rate	20 msec	
BACnet MS/TP Master		
Operation Mode	BACnet MS/TP Master Initiator	
Supported Object Types	Device, BI/BO/BV, AI/AO/AV, MI/MO/MV, Character String Value	
Supported Service Codes	Read Property-A, Read Property Multiple-A, Write Property-A, Write Property Multiple-A, Device Dynamic Binding-A	
Maximum Connections	32	
Number Read/Write Scan Lines per Device	200 Total - 100 reads & 100 writes	
Scan Line Support	Up to 128 Objects	
INCLUDED WITH GATEWAY		
3' power cable with flying leads	5-year hardware warranty	
IPSetup software – automatically locates RTA gateway on the network	Unlimited firmware feature upgrades for life	
CAT5 crossover cable for direct connection to PC during programming	Complete, unlimited access to our industry leading support staff	
Manual		

ELECTRICAL / ENVIRONMENT	AL	
DC Input Voltage	12-24 VDC	
Maximum Baud Rate	115K baud	DIN Rail Mou
Operating Temperature	-40 C to 85 C	
Certification	RoHS-Compliant, UL, CUL, CE Approvals	
ENCLOSURE / HARDWARE		,
Size	3.88" x 2.57" x 1.06"	
Weight	5.5 oz	
Enclosure Type	Anodized Aluminum	
Mounting	Din rail or panel mount	2.57
LEDs	Power LED & 2 general purpose LEDs on side	1
GATEWAY FEATURES & FUN		l dr
	Set <, <=, >, >=, ==, !=, and change-of-state rules	
Alarming	on any data moving through the gateway. If alarm	
3	rule is triggered an email notification can be sent.	·
	You can configure up to 9 different users access to	
Gateway Security	diagnostic and configuration screens.	
	diagnostic and comiguration solecitis.	1
	Allows for data manipulation during protocol	400
Translation Table	translation. Scaling and other data format changes	1.06
	can occur in the gateway.	
	,	
	Protocol specific status, counters, and error	NOT EXA
	messages are accessible within the gateway's	Real Time Au
Status and Counters	diagnostics page. They can also be delivered to a	Give us a ca
	connected device.	<u>www.rt</u>
		Cu
	Allana mana ta ana and lan ataut ma angunana	
Diagnostic Logging Page	Allows users to see and log start up sequences,	
2 00 0	protocol specific messages & error messages.	

Note: All dimensions are in Inches		 3.88
00000	2.57	
		99999 99

NOT EXACTLY WHAT YOU WERE LOOKING FOR? Real Time Automation offers a full line of gateway products. Give us a call at 1-800-249-1612. Or, check out a listing at www.rtautomation.com/products. We also offer customizations for unique applications.

CATALOG #	DESCRIPTION
460ECBM-NNA4	Connects up to 32 EtherNet/IP adapters with a BACnet MS/TP master



Made in the

U.S.A.



Always In







