

CONTACT US! 1-800-249-1612 rtautomation.com

Real Time Automation Gateways

460ECMM-N700

EtherNet/IP to Modbus RTU Slave

FEATURES

- Fully configurable
 EtherNet/IP scanner
- Map data from up to 32 EtherNet/IP adapters
- Fully configurable Modbus RTU master
- Connects up to 32 Modbus RTU slaves
- Effortless Browser Based Configuration, no programming software is required
- Simple data translation allows you to manipulate data as it passes between protocols
- Guaranteed Stock
- 5-Year Hardware Warranty

Connect EtherNet/IP Adapter Devices to Modbus RTU Slaves

The 460ECMM moves registers and coils between Modbus RTU slave devices and an EtherNet/IP network of adapter devices. It's the perfect tool to tie in all of your EtherNet/IP devices into your Modbus RTU network.

Easily interface existing device networks without having to add a controller.

How Do I Use the 460ECMM-N700 in My Application?


For most applications, the mapping is very straightforward. Modbus register and coil data is mapped to up 496 bytes of EtherNet/IP data per adapter. EtherNet/IP IO data is mapped directly to your Modbus RTU slave registers and coils.

It really is that simple.

Why Use Real Time Automation as a Gateway Supplier?

While there are certainly other companies offering protocol gateways, there is no one who provides the level of support and service that you receive from RTA.

When you call, a live person answers the phone. When you talk with sales, you will get honest answers and recommendations. When you get support, it is from an engineer who had a hand in the product's development, and support doesn't require a ticket or 24-hour wait.



A Solution, A Philosophy, the RTA Way. We understand the long hours spent on a factory floor and the pressure to keep a line running and product flowing. That's how Real Time Automation came to be. You want easy-to-use solutions where the hardest part is to open the box. You need customer support second to none. If you get all that and a fun customer experience all the better. Thirty years later, our mission remains the same: To move your data where you need it, when you need it, and how you need it.

Specification

EtherNet/IP Scanner	
Operation Mode	Class 1 I/O Scanner
Message Support	Implicit Class 1 Cyclic I/O, Explicit not supported
Data Types	BIT8,16 & 32; INT8, 16, 32 & 64; UINT8,16, 32 & 64; Float & Double
Maximum EtherNet/IP Adapter Devices	32
Max Data Per Adapter Connection	Up to 496 bytes in each direction
Maximum IO Scan Rate	20 msec
Modbus RTU Master	
Operation Mode	Modbus RTU Master
Function Codes Supported	1,2,3,4,5,6, 15 & 16
Swapping	Byte and Word Swapping
Maximum Modbus RTU Slave Devices	32
Number Read/Write Scan Lines per RTU Slave Device	200 Total - 100 reads & 100 writes
Scan Line Support	Up to 125 Registers or 512 Coils
INCLUDED WITH GATEWAY	
3' power cable with flying leads	5-year hardware warranty
IPSetup software – automatically locates RTA gateway on the network	Unlimited firmware feature upgrades for life
CAT5 crossover cable for direct connection to PC during programming	Complete, unlimited access to our industry leading support staff
Manual	

ELECTRICAL / ENVIRONMENTAL DC Input Voltage

LEEOINGAE, ENVIRONMENT,		
DC Input Voltage	12-24 VDC	
Maximum Baud Rate	115K baud	
Operating Temperature	-40 C to 85 C	
Certification	RoHS-Compliant, UL, CUL, CE Approvals	
ENCLOSURE / HARDWARE		Ithernet
Size	4.19" x 3.25" x 1"	
Weight	6.5 oz	3.25
Enclosure Type	Anodized Aluminum	I I I I
Mounting	Din rail or panel mount	Note
LEDs	Power LED, Ethernet link/data LED, & Ethernet speed LED	
GATEWAY FEATURES & FUNC	TIONS	- 100
Alarming	Set <, <=, >, >=, ==, !=, and change-of-state rules on any data moving through the gateway. If alarm rule is triggered an email notification can be sent.	Din Rail
Gateway Security	You can configure up to 9 different users access to diagnostic and configuration screens.	Panel Mount
Translation Table	Allows for data manipulation during protocol translation. Scaling and other data format changes can occur in the gateway.	
Status and Counters	Protocol specific status, counters, and error messages are accessible within the gateway's diagnostics page. They can also be delivered to a connected device.	NOT EXACTLY W Real Time Automation Give us a call at 1-80 www.rtautomat customizati
Diagnostic Logging Page	Allows users to see and log start up sequences, protocol specific messages & error messages.	

Litre (net	Port	00000
3.25	Port	() () () () () () () () () () () () () (
	-	
Din Rail	I	
Panel Mount	=	

WHAT YOU WERE LOOKING FOR? on offers a full line of gateway products. 800-249-1612. Or, check out a listing at ation.com/products. We also offer ations for unique applications.

CATALOG #	DESCRIPTION
460ECMM-N700	Connects up to 32 EtherNet/IP adapters with as many as 32 Modbus RTU slave devices













Real Time Automation, Inc.

solutions@rtautomation.com

1-800-249-1612