CONTACT US!

1-800-249-1612 rtautomation.com

Real Time Automation Gateways

460ECPS-N2EW

EtherNet/IP to PROFINET IO

FEATURES

- Fully configurable EtherNet/IP scanner
- Map data from up to 32 EtherNet/IP adapters
- Fully configurable **PROFINET** device
- Supports up to 1280 bytes of data in each direction on PROFINET IO
- **Effortless Browser** Based Configuration, no programming software is required
- Simple data translation allows you to manipulate data as it passes between protocols
- **Guaranteed Stock**
- 5-Year Hardware Warranty

Connect EtherNet/IP Adapters to a PROFINET IO Controller

The 460ECPS moves data between up to 32 EtherNet/IP adapters and a PROFINET IO controller. It's the perfect tool to connect EtherNet/IP devices into your PROFINET controller.

Best of all, the product is made in the USA, always in stock, and comes with 5-year warranty.

How Do I Use the 460ECPS-N2EW in My Application?

EtherNet/IP data will be mapped into 10 PROFINET slots. The gateway can move up 1280 bytes of data in each direction.

It's really that simple. Need to modify your data as it passes from one protocol to the other? No problem. Each data mapping you apply can be modified with up to three mathematic functions. Add 4 to a value, multiply by 4 and divide by 10 with ease.

Why Use Real Time Automation as a Gateway Supplier?

While there are certainly other companies offering protocol gateways, there is no one who provides the level of support and service that you receive from RTA.

When you call, a live person answers the phone. When you talk with sales, you will get honest answers and recommendations. When you get support, it is from an engineer who had a hand in the product's development, and support doesn't require a ticket or 24-hour wait.



A Solution, A Philosophy, the RTA Way. We understand the long hours spent on a factory floor and the pressure to keep a line running and product flowing. That's how Real Time Automation came to be. You want easy-to-use solutions where the hardest part is to open the box. You need customer support second to none. If you get all that and a fun customer experience all the better. Thirty years later, our mission remains the same: To move your data where you need it, when you need it, and how you need it.

Specification

EtherNet/IP Scanner	
Operation Mode	Class 1 I/O Scanner
Message Support	Implicit Class 1 Cyclic I/O, Explicit not supported
Data Types	BIT8,16 & 32; INT8, 16, 32 & 64; UINT8,16, 32 & 64; Float & Double
Maximum EtherNet/IP Adapter Devices	32
Max Data Per Adapter Connection	Up to 496 bytes in each direction
Maximum IO Scan Rate	20 msec
Profinet IO Server	
Maximum Number of Slots	10 Slots in, 10 Slots out
Slot Data Segment Sizes	8, 16, 32, 64 or 128 Bytes
Each Slot Can be Defined for a Single Data Type of	Int8, int16, int32, int64, UInt8, Uint16, Uint32, Uint64, float, double, binary8, binary16 or binary32, Short String
Total Data Supported in Each Direction	1280 Bytes
Maximum Profinet IO Controller Connections	1
String Support	1 string per slot
INCLUDED WITH GATEWAY	
3' power cable with flying leads	5-year hardware warranty
IPSetup software – automatically locates RTA gateway on the network	Unlimited firmware feature upgrades for life
CAT5 crossover cable for direct connection to PC during programming	Complete, unlimited access to our industry leading support staff
Manual	

ELECTRICAL / ENVIRONMENTAL		
DC Input Voltage	12-24 VDC	
Maximum Baud Rate	115K baud	F
Operating Temperature	-40 C to 85 C	
Certification	RoHS-Compliant, UL, CUL, CE Approvals, Class I Div 2	-
ENCLOSURE / HARDWARE		
Size	5.40" x 3.83" x 1.19"	
Weight	7.6 oz	
Enclosure Type	Anodized Aluminum	
Mounting	Din rail or panel mount	
LEDs	Power LED & 2 general purpose LEDs on side	
GATEWAY FEATURES & FUNCTIO	NS .	
Alarming	Set <, <=, >, >=, ==, !=, and change-of-state rules on any data moving through the gateway. If alarm rule is triggered an email notification can be sent.	®
Gateway Security	You can configure up to 9 different users access to diagnostic and configuration screens.	
Translation Table	Allows for data manipulation during protocol translation. Scaling and other data format changes can occur in the gateway.	
Status and Counters	Protocol specific status, counters, and error messages are accessible within the gateway's diagnostics page. They can also be delivered to a connected device.	NOT EXACTLY WHA Real Time Automation o Give us a call at 1-800-; www.rtautomation customization
Diagnostic Logging Page	Allows users to see and log start up sequences, protocol specific messages & error messages.	

3.83	
NOT EXACTLY WHAT YOU WERE LOOKING FOR?	

NOT EXACTLY WHAT YOU WERE LOOKING FOR?
Real Time Automation offers a full line of gateway products.
Give us a call at 1-800-249-1612. Or, check out a listing at
www.rtautomation.com/products. We also offer
customizations for unique applications.

CATALOG #	DESCRIPTION
460ECPS-N2EW	Connects up to 32 EtherNet/IP adapters with a PROFINET IO controller



Made in the

U.S.A.



Always In

Stock





