CONTACT US!

1-800-249-1612 rtautomation.com

Real Time Automation Gateways

460ESMRS-N2EW

EtherNet/IP to Modbus RTU Master

FEATURES

- Fully configurable
 EtherNet/IP adapter
- Supports up To 480 bytes of input and 480 bytes of output data
- Fully configurable Modbus RTU slave
- Move up to 100 groups of 512 contiguous coils or 512 contiguous registers to or from your Modbus RTU master
- Effortless Browser
 Based Configuration,
 no programming
 software is required
- Simple data translation allows you to manipulate data as it passes between protocols
- Guaranteed Stock
- 5-Year Hardware Warranty

Connect a Modbus RTU Controller to an EtherNet/IP PLC

The 460ESMRS allows you to connect a Modbus RTU master to an EtherNet/IP controller. It's the perfect solution to integrate legacy Modbus controllers and utilize new cost effect Modbus controllers in your EtherNet/IP architecture.

Best of all, the product is made in the USA, is always in stock, and comes with 5-year warranty.

How Do I Use the 460ESMRS-N2EW in My Application?

The mapping is very straightforward. Modbus register and coil data is mapped to EtherNet/IP IO blocks. Up to 480 bytes of data can be mapped in each direction between the protocols.

It really is that simple.

Why Use Real Time Automation as a Gateway Supplier?

While there are certainly other companies offering protocol gateways, there is no one who provides the level of support and service that you receive from RTA.

When you call, a live person answers the phone. When you talk with sales, you will get honest answers and recommendations. When you get support, it is from an engineer who had a hand in the product's development, and support doesn't require a ticket or 24-hour wait.



A Solution, A Philosophy, the RTA Way. We understand the long hours spent on a factory floor and the pressure to keep a line running and product flowing. That's how Real Time Automation came to be. You want easy-to-use solutions where the hardest part is to open the box. You need customer support second to none. If you get all that and a fun customer experience all the better. Thirty years later, our mission remains the same: To move your data where you need it, when you need it, and how you need it.

| EtherNet/IP Adapter | |
|---|--|
| Operation Mode | Class 1 I/O Adapter |
| Message Support | Implicit Class 1 Cyclic I/O, Explicit Class 3 and UCMM Supported |
| Data Types | BIT8,16 & 32; INT8, 16, 32 & 64; UINT8,16, 32 & 64; Float & Double |
| Maximum EtherNet/IP Scanner Devices | Up to 10 can listen, only 1 can write I/O |
| Maximum Data Supported | Up to 480 bytes in each direction |
| Maximum IO Scan Rate | 20 msec |
| Modbus RTU Slave | |
| Operation Mode | Modbus RTU Slave |
| Function Codes Supported | 1,2,3,4,5,6, 15 & 16 |
| Swapping | Byte and Word Swapping |
| Maximum Modbus RTU Master Connections | 1 |
| Contiguous Data Areas | 200 Total - 100 reads & 100 writes |
| Data Area Limits | 512 Contiguous Coils or 512 Contiguous Registers |
| INCLUDED WITH GATEWAY | |
| 3' power cable with flying leads | 5-year hardware warranty |
| IPSetup software – automatically locates RTA gateway on the network | Unlimited firmware feature upgrades for life |
| CAT5 crossover cable for direct connection to PC during programming | Complete, unlimited access to our industry leading support staff |
| Manual | |

| ELECTRICAL / ENVIRONMENTAL | | |
|------------------------------|---|--|
| DC Input Voltage | 12-24 VDC | |
| Maximum Baud Rate | 115K baud | F |
| Operating Temperature | -40 C to 85 C | |
| Certification | RoHS-Compliant, UL, CUL, CE Approvals, Class I Div 2 | 3.83 |
| ENCLOSURE / HARDWARE | | |
| Size | 5.40" x 3.83" x 1.19" | |
| Weight | 7.6 oz | |
| Enclosure Type | Anodized Aluminum | |
| Mounting | Din rail or panel mount | |
| LEDs | Power LED & 2 general purpose LEDs on side | |
| GATEWAY FEATURES & FUNCTIONS | | |
| Alarming | Set <, <=, >, >=, ==, !=, and change-of-state rules on any data moving through the gateway. If alarm rule is triggered an email notification can be sent. | |
| Gateway Security | You can configure up to 9 different users access to diagnostic and configuration screens. | |
| Translation Table | Allows for data manipulation during protocol translation. Scaling and other data format changes can occur in the gateway. | |
| Status and Counters | Protocol specific status, counters, and error messages are accessible within the gateway's diagnostics page. They can also be delivered to a connected device. | NOT EXACTLY WHAT YOU WERE LOOKING FOR? Real Time Automation offers a full line of gateway products. Give us a call at 1-800-249-1612. Or, check out a listing at www.rtautomation.com/products . We also offer customizations for unique applications. |
| Diagnostic Logging Page | Allows users to see and log start up sequences, protocol specific messages & error messages. | |

| CATALOG # | DESCRIPTION |
|---------------|--|
| 460ESMRS-N2EW | Connects an EtherNet/IP scanner with a Modbus RTU master |



Made in the

U.S.A.



Always In





