

CONTACT US! 1-800-249-1612 rtautomation.com

## 460MCBM-N34

### Modbus TCP/IP to BACnet MS/TP

#### **FEATURES**

- Fully configurable Modbus TCP/IP client
- Connects up to 32 Modbus TCP/IP servers
- Fully configurable BACnet MS/TP master
- BACnet MS/TP supports device, binary I/O/V, analog I/O/V, multi-state I/O/V, and character string value object types
- Effortless Browser Based Configuration, no programming software is required
- Simple data translation allows you to manipulate data as it passes between protocols
- Guaranteed Stock
- 5-Year Hardware Warranty

#### **Connect Modbus TCP/IP Servers to BACnet MS/TP Devices**

The 460MCBM moves data between a network of up to 32 Modbus TCP/IP servers and up to 32 BACnet MS/TP devices.

It's a perfect tool to move data between your Modbus power meters, boilers, chillers, and other server devices and your BACnet MS/TP devices.

#### How Do I Use the 460MCBM-N34 in My Application?

For most applications, the mapping is very straightforward. Modbus register data is mapped to BACnet analog objects and Modbus coil data is mapped to binary objects. The only additional piece required for BACnet is adding metadata to each object.

It really is that simple.

#### Why Use Real Time Automation as a Gateway Supplier?

While there are certainly other companies offering protocol gateways, there is no one who provides the level of support and service that you receive from RTA.

When you call, a live person answers the phone. When you talk with sales, you will get honest answers and recommendations. When you get support, it is from an engineer who had a hand in the product's development, and support doesn't require a ticket or 24-hour wait.



A Solution, A Philosophy, the RTA Way. We understand the long hours spent on a factory floor and the pressure to keep a line running and product flowing. That's how Real Time Automation came to be. You want easy-to-use solutions where the hardest part is to open the box. You need customer support second to none. If you get all that and a fun customer experience all the better. Thirty years later, our mission remains the same: To move your data where you need it, when you need it, and how you need it.

# Specification

| Modbus TCP Client  |   |  |
|--|---|--|
| Operation Mode   | Modbus TCP/IP Client  |  |
| Function Codes Supported   | 1,2,3,4,5,6, 15 & 16  |  |
| Swapping   | Byte and Word Swapping  |  |
| Maximum Modbus TCP/IP Server Devices                                   | 32  |  |
| Number Read/Write Scan Lines per Server Device                         | 200 Total - 100 reads & 100 writes  |  |
| Scan Line Support  | Up to 125 Registers or 512 Coils  |  |
| BACnet MS/TP Master  |   |  |
| Operation Mode   | BACnet MS/TP Master Initiator   |  |
| Supported Object Types   | Device, BI/BO/BV, AI/AO/AV, MI/MO/MV, Character String Value  |  |
| Supported Service Codes  | Read Property-A, Read Property Multiple-A, Write Property-A, Write Property Multiple-A, Device<br>Dynamic Binding-A |  |
| Maximum Connections  | 32  |  |
| Number Read/Write Scan Lines per Device                                | 200 Total - 100 reads & 100 writes  |  |
| Scan Line Support  | Up to 128 Objects   |  |
| INCLUDED WITH GATEWAY  |   |  |
| 3' power cable with flying leads                                       | 5-year hardware warranty  |  |
| IPSetup software – automatically locates RTA<br>gateway on the network | Unlimited firmware feature upgrades for life  |  |
| CAT5 crossover cable for direct connection to PC during programming    | Complete, unlimited access to our industry leading support staff  |  |
| Manual   |   |  |

| ELECTRICAL / ENVIRONMEN      | TAL   |   |
|------------------------------|---|---|
| DC Input Voltage             | 8 VDC @ 230mA to 28 VDC @ 80 mA   |   |
| Maximum Baud Rate            | 115K baud   | LEOs  |
| Operating Temperature        | -40 C to 85 C   |   |
| Certification                | RoHS-Compliant, UL, CUL, CE Approvals, Class<br>I Div 2   |   |
| ENCLOSURE / HARDWARE         |   |   |
| Size                         | 4.2" x 3.25" x 1"   |   |
| Weight                       | 7 oz  | 3.25  |
| Enclosure Type               | Anodized Aluminum   |   |
| Mounting                     | Din rail or panel mount   |   |
| LEDs                         | Ethernet link/data LED, Ethernet speed LED,<br>power LED, & 2 general purpose LEDs on side  |   |
| GATEWAY FEATURES & FUNCTIONS |   | 1.00 4.19 1.00  |
| Alarming                     | Set <, <=, >, >=, ==, !=, and change-of-state rules<br>on any data moving through the gateway. If alarm<br>rule is triggered an email notification can be sent. | Din Rail  |
| Gateway Security             | You can configure up to 9 different users access to diagnostic and configuration screens.   | Panel Mount   |
| Translation Table            | Allows for data manipulation during protocol translation. Scaling and other data format changes can occur in the gateway.                                       |   |
| Status and Counters          | Protocol specific status, counters, and error messages are accessible within the gateway's diagnostics page. They can also be delivered to a connected device.  | NOT EXACTLY WHAT YOU WERE LOOKING FOR?<br>Real Time Automation offers a full line of gateway products.<br>Give us a call at 1-800-249-1612. Or, check out a listing at<br>www.rtautomation.com/products. We also offer<br>customizations for unique applications. |
| Diagnostic Logging Page      | Allows users to see and log start up sequences, protocol specific messages & error messages.  |   |
| CATALOG #                    | DESCRIPTION   | NE YEAR   |
| 460MCBM-N34                  | Connects up to 32 Modbus TCP servers with as<br>BACnet MS/TP slaves   | s many as 32  |

Made in the



Always In Stock





**Real Time Automation, Inc.** 

solutions@rtautomation.com

1-800-249-1612