CONTACT US!

1-800-249-1612 rtautomation.com

Real Time Automation Gateways

460MCMM-N700

Modbus RTU to Modbus TCP/IP

FEATURES

- Fully configurable Modbus TCP/IP client
- Connects up to 32
 Modbus TCP/IP servers
- Fully configurable
 Modbus RTU master
- Connects up to 32
 Modbus RTU slaves
- Effortless Browser
 Based Configuration,
 no programming
 software is required
- Simple data translation allows you to manipulate data as it passes between protocols
- Guaranteed Stock
- 5-Year Hardware Warranty

Get Your Modbus RTU Slave Devices Connected to Modbus TCP/IP Server Devices

The 460MCMM moves data between up to 32 Modbus TCP/IP server devices and up to 32 Modbus RTU slave devices.

With the 460MCMM, register and coil data can be freely moved between your Modbus RTU and Modbus TCP/IP networks.

How Do I Use the 460MCMM-N700 in My Application?


To your Modbus TCP/IP server devices, the gateway will look like any other Modbus TCP/IP client controller. To your Modbus RTU slaves, the gateway acts as a Modbus RTU master. In the gateway, you configure what data will be exchanged.

In the translation, you are able to map register and coil data from any device to any other device connected to the gateway.

Why Use Real Time Automation as a Gateway Supplier?

While there are certainly other companies offering protocol gateways, there is no one who provides the level of support and service that you receive from RTA.

When you call, a live person answers the phone. When you talk with sales, you will get honest answers and recommendations. When you get support, it is from an engineer who had a hand in the product's development, and support doesn't require a ticket or 24-hour wait.



A Solution, A Philosophy, the RTA Way. We understand the long hours spent on a factory floor and the pressure to keep a line running and product flowing. That's how Real Time Automation came to be. You want easy-to-use solutions where the hardest part is to open the box. You need customer support second to none. If you get all that and a fun customer experience all the better. Thirty years later, our mission remains the same: To move your data where you need it, when you need it, and how you need it.

Modbus TCP Client	
Operation Mode	Modbus TCP/IP Client
Function Codes Supported	1,2,3,4,5,6, 15 & 16
Swapping	Byte and Word Swapping
Maximum Modbus TCP/IP Server Devices	32
Number Read/Write Scan Lines per Server Device	200 Total - 100 reads & 100 writes
Scan Line Support	Up to 125 Registers or 512 Coils
Modbus RTU Master	
Operation Mode	Modbus RTU Master
Function Codes Supported	1,2,3,4,5,6, 15 & 16
Swapping	Byte and Word Swapping
Maximum Modbus RTU Slave Devices	32
Number Read/Write Scan Lines per RTU Slave Device	200 Total - 100 reads & 100 writes
Scan Line Support	Up to 125 Registers or 512 Coils
INCLUDED WITH GATEWAY	
3' power cable with flying leads	5-year hardware warranty
IPSetup software – automatically locates RTA gateway on the network	Unlimited firmware feature upgrades for life
CAT5 crossover cable for direct connection to PC during programming	Complete, unlimited access to our industry leading support staff
Manual	

ELECTRICAL / ENVIRONMEN	TAL		
DC Input Voltage	12-24 VDC		
Maximum Baud Rate	115K baud		
Operating Temperature	-40 C to 85 C		b (8)
Certification	RoHS-Compliant, UL, CUL, CE Approvals	112	5 69
ENCLOSURE / HARDWARE		Ithernet	8 8
Size	4.19" x 3.25" x 1"		
Weight	6.5 oz	3,26	
Enclosure Type	Anodized Aluminum	<u> </u>	2 (8)
Mounting	Din rail or panel mount	Note: All dimension	8 000
LEDs	Power LED, Ethernet link/data LED, & Ethernet speed LED	are in inches	
GATEWAY FEATURES & FU	NCTIONS		-100
Alarming	Set <, <=, >, >=, ==, !=, and change-of-state rules on any data moving through the gateway. If alarm rule is triggered an email notification can be sent.	Din Rail	-
Gateway Security	You can configure up to 9 different users access to diagnostic and configuration screens.	Panel Mount	
Translation Table	Allows for data manipulation during protocol translation. Scaling and other data format changes can occur in the gateway.		
Status and Counters	Protocol specific status, counters, and error messages are accessible within the gateway's diagnostics page. They can also be delivered to a connected device.	NOT EXACTLY WHAT YOU WERE LOOKING FOR? Real Time Automation offers a full line of gateway products. Give us a call at 1-800-249-1612. Or, check out a listing at www.rtautomation.com/products . We also offer customizations for unique applications.	
Diagnostic Logging Page	Allows users to see and log start up sequences, protocol specific messages & error messages.		NAME.
2474.22 "	DECORPTION .		

CATALOG #	DESCRIPTION
460MCMM-N700	Connects up to 32 Modbus TCP servers with as many as 32 Modbus RTU slaves



Made in the

U.S.A.



Always In







