CONTACT US!

1-800-249-1612 rtautomation.com

Real Time Automation Gateways

460MMDFM-N700

Connect Modbus RTU Slaves to Legacy Serial DF1 PLCs

FEATURES

- Fully configurable Modbus RTU master
- Connects up to 32
 Modbus RTU slaves
- Support for PLC5, SLC and MicroLogix PLCs
- Connect up to 32 DF1 serial devices
- Effortless Browser
 Based Configuration,
 no programming
 software is required
- Simple data translation allows you to manipulate data as it passes between protocols
- Guaranteed Stock
- 5-Year Hardware Warranty

Connect Up To 32 Modbus RTU Slave Devices to a Serial PLC5, SLC or MicroLogix PLC

You can now connect a network of up to 32 Modbus RTU slaves to a legacy Allen-Bradley PLC over DF1.

It's the perfect tool to save legacy PLCs from the scrap pile and extend their useful life.

How Do I Use the 460MMDFM-N700 in My Application?

The mapping is very straightforward. Modbus register and coil data is mapped to files in the PLCs data tables. For example, you can map N7:200 to Modbus register 40200 in Modbus slave 10. Data transfer is bidirectional.

It really is that simple.

Why Use Real Time Automation as a Gateway Supplier?

While there are certainly other companies offering protocol gateways, there is no one who provides the level of support and service that you receive from RTA.

When you call, a live person answers the phone. When you talk with sales, you will get honest answers and recommendations. When you get support, it is from an engineer who had a hand in the product's development, and support doesn't require a ticket or 24-hour wait.



A Solution, A Philosophy, the RTA Way. We understand the long hours spent on a factory floor and the pressure to keep a line running and product flowing. That's how Real Time Automation came to be. You want easy-to-use solutions where the hardest part is to open the box. You need customer support second to none. If you get all that and a fun customer experience all the better. Thirty years later, our mission remains the same: To move your data where you need it, when you need it, and how you need it.

Modbus RTU Master		
Operation Mode	Modbus RTU Master	
Function Codes Supported	1,2,3,4,5,6, 15 & 16	
Swapping	Byte and Word Swapping	
Maximum Modbus RTU Slave Devices	32	
Number Read/Write Scan Lines per RTU Slave Device	200 Total - 100 reads & 100 writes	
Scan Line Support	Up to 125 Registers or 512 Coils	
DF1 Master		
Operation Mode	DF1 Master Full Duplex and DF1 Master Half Duplex	
PLCs Supported	MicroLogix 1000, SLC 5/03 5/04 5/05, most PLC5s	
Maximum number of Devices supported	1 in Full Duplex Mode, 32 in Half Duplex	
Data Type Supported	100 Integers or 100 Binaries, or 50 floats, 82 character string per Scan line	
Scan Lines	100 input / 100 output	
Physical Connections	RS-485 and RS-232	
INCLUDED WITH GATEWAY		
3' power cable with flying leads	5-year hardware warranty	
IPSetup software – automatically locates RTA gateway on the network	Unlimited firmware feature upgrades for life	
CAT5 crossover cable for direct connection to PC during programming	Complete, unlimited access to our industry leading support staff	
Optional: Generic 1761-CBL-PM02 Cable	Optional: NULL Modem Cable	

12-24 VDC 115K baud -40 C to 85 C RoHS-Compliant, UL, CUL, CE Approvals 4.19" x 3.25" x 1" 6.5 oz Anodized Aluminum Din rail or panel mount Power LED, Ethernet link/data LED, & Ethernet speed LED NS Set <, <=, >, >=, ==, !=, and change-of-state rules on any data moving through the gateway. If alarm rule is triggered an email notification can be sent. You can configure up to 9 different users access to diagnostic and configuration screens.	3.25 Note: At dimension are ninches Din Rail
-40 C to 85 C RoHS-Compliant, UL, CUL, CE Approvals 4.19" x 3.25" x 1" 6.5 oz Anodized Aluminum Din rail or panel mount Power LED, Ethernet link/data LED, & Ethernet speed LED NS Set <, <=, >, >=, ==, !=, and change-of-state rules on any data moving through the gateway. If alarm rule is triggered an email notification can be sent. You can configure up to 9 different users access to	Note: At dimension are ninches 1.00 4.19
RoHS-Compliant, UL, CUL, CE Approvals 4.19" x 3.25" x 1" 6.5 oz Anodized Aluminum Din rail or panel mount Power LED, Ethernet link/data LED, & Ethernet speed LED NS Set <, <=, >, >=, ==, !=, and change-of-state rules on any data moving through the gateway. If alarm rule is triggered an email notification can be sent. You can configure up to 9 different users access to	Note: Al dimension are n inches
4.19" x 3.25" x 1" 6.5 oz Anodized Aluminum Din rail or panel mount Power LED, Ethernet link/data LED, & Ethernet speed LED NS Set <, <=, >, >=, ==, !=, and change-of-state rules on any data moving through the gateway. If alarm rule is triggered an email notification can be sent. You can configure up to 9 different users access to	Note: Al dimension are n inches
6.5 oz Anodized Aluminum Din rail or panel mount Power LED, Ethernet link/data LED, & Ethernet speed LED NS Set <, <=, >, >=, ==, !=, and change-of-state rules on any data moving through the gateway. If alarm rule is triggered an email notification can be sent. You can configure up to 9 different users access to	Note: Al dimension are n inches
6.5 oz Anodized Aluminum Din rail or panel mount Power LED, Ethernet link/data LED, & Ethernet speed LED NS Set <, <=, >, >=, ==, !=, and change-of-state rules on any data moving through the gateway. If alarm rule is triggered an email notification can be sent. You can configure up to 9 different users access to	Note: All dimension are in inches 1.00 - 4.19
Anodized Aluminum Din rail or panel mount Power LED, Ethernet link/data LED, & Ethernet speed LED NS Set <, <=, >, >=, ==, !=, and change-of-state rules on any data moving through the gateway. If alarm rule is triggered an email notification can be sent. You can configure up to 9 different users access to	Note: All dimension are in inches 1.00 - 4.19
Din rail or panel mount Power LED, Ethernet link/data LED, & Ethernet speed LED NS Set <, <=, >, >=, ==, !=, and change-of-state rules on any data moving through the gateway. If alarm rule is triggered an email notification can be sent. You can configure up to 9 different users access to	-1.00 - 4.19 - 1.00 -
Power LED, Ethernet link/data LED, & Ethernet speed LED NS Set <, <=, >, >=, ==, !=, and change-of-state rules on any data moving through the gateway. If alarm rule is triggered an email notification can be sent. You can configure up to 9 different users access to	-1.00 - 4.19 - 1.00 -
speed LED NS Set <, <=, >, >=, ==, !=, and change-of-state rules on any data moving through the gateway. If alarm rule is triggered an email notification can be sent. You can configure up to 9 different users access to	-1.00 - 4.19 - 1.00 -
Set <, <=, >, >=, ==, !=, and change-of-state rules on any data moving through the gateway. If alarm rule is triggered an email notification can be sent. You can configure up to 9 different users access to	—1.60— Din Rail
on any data moving through the gateway. If alarm rule is triggered an email notification can be sent. You can configure up to 9 different users access to	Din Rail
e i	
diagnostic and configuration screens.	Panel Mount
Allows for data manipulation during protocol translation. Scaling and other data format changes can occur in the gateway.	••••
Protocol specific status, counters, and error messages are accessible within the gateway's diagnostics page. They can also be delivered to a connected device.	NOT EXACTLY WHAT YOU WERE LOOKING FOR? Real Time Automation offers a full line of gateway products. Give us a call at 1-800-249-1612. Or, check out a listing at www.rtautomation.com/products . We also offer customizations for unique applications.
Allows users to see and log start up sequences, protocol specific messages & error messages.	
	translation. Scaling and other data format changes can occur in the gateway. Protocol specific status, counters, and error messages are accessible within the gateway's diagnostics page. They can also be delivered to a connected device. Allows users to see and log start up sequences,

CATALOG #	DESCRIPTION
460MMDFM-N700	Connects up to 32 Modbus RTU slaves with as many as 32 DF1 slaves



Made in the

U.S.A.



Always In





