## CONTACT US!

1-800-249-1612 rtautomation.com

# **Real Time Automation Gateways**

# 460MRSBC-N700

### Modbus RTU to BACnet/IP

#### **FEATURES**

- Fully configurable Modbus RTU slave
- Move up to 100 groups of 512 contiguous coils or 512 contiguous registers to or from your Modbus RTU master
- Fully configurable BACnet/IP client
- BACnet/IP supports device, binary I/O/V, analog I/O/V, multistate I/O/V, and character string value object types
- Effortless Browser
   Based Configuration,
   no programming
   software is required
- Simple data translation allows you to manipulate data as it passes between protocols
- Guaranteed Stock
- 5-Year Hardware Warranty

#### Connect BACnet/IP Servers to a Modbus RTU Master

The 460MRSBC moves data between a Modbus RTU master device and up to 32 BACnet/IP server devices.

The 460MRSBC module bundles your BACnet/IP data and makes it available as Modbus RTU data. The module provides complete Modbus RTU slave and BACnet/IP client capability.

### How Do I Use the 460MRSBC-N700 in My Application?


To your Modbus RTU master device, the gateway acts as a Modbus RTU slave. To your BACnet/IP server devices, the gateway acts as a BACnet/IP client.

You can both send data to your BACnet/IP server devices and read current status data. Up to 1200 analog and 1600 binary objects can be mapped into or out of up to 512 contiguous registers and coils in the Modbus RTU master.

### Why Use Real Time Automation as a Gateway Supplier?

While there are certainly other companies offering protocol gateways, there is no one who provides the level of support and service that you receive from RTA.

When you call, a live person answers the phone. When you talk with sales, you will get honest answers and recommendations. When you get support, it is from an engineer who had a hand in the product's development, and support doesn't require a ticket or 24-hour wait.



A Solution, A Philosophy, the RTA Way. We understand the long hours spent on a factory floor and the pressure to keep a line running and product flowing. That's how Real Time Automation came to be. You want easy-to-use solutions where the hardest part is to open the box. You need customer support second to none. If you get all that and a fun customer experience all the better. Thirty years later, our mission remains the same: To move your data where you need it, when you need it, and how you need it.

Modbus RTU Slave			
Operation Mode	Modbus RTU Slave		
Function Codes Supported	1,2,3,4,5,6, 15 & 16		
Swapping	Byte and Word Swapping		
Maximum Modbus RTU Master Connections	1		
Contiguous Data Areas	200 Total - 100 reads & 100 writes		
Data Area Limits	512 Contiguous Coils or 512 Contiguous Registers		
BACnet/IP Client			
Operation Mode	BACnet/IP Client		
Supported Object Types	Device, BI/BO/BV, AI/AO/AV, MI/MO/MV, Character String Value		
Supported Service Codes	Read Property-A, Read Property Multiple-A, Write Property-A, Write Property Multiple-A, Device Dynamic Binding-A		
Maximum Connections	32		
Number Read/Write Scan Lines per Device	200 Total - 100 reads & 100 writes		
Scan Line Support	Up to 128 Objects		
INCLUDED WITH GATEWAY			
3' power cable with flying leads	5-year hardware warranty		
IPSetup software – automatically locates RTA gateway on the network	Unlimited firmware feature upgrades for life		
CAT5 crossover cable for direct connection to PC during programming	Complete, unlimited access to our industry leading support staff		
Manual			

ELECTRICAL / ENVIRONMENT	AL	
DC Input Voltage	12-24 VDC	
Maximum Baud Rate	115K baud	
Operating Temperature	-40 C to 85 C	
Certification	RoHS-Compliant, UL, CUL, CE Approvals	
ENCLOSURE / HARDWARE		Ithernet 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0
Size	4.19" x 3.25" x 1"	
Weight	6.5 oz	3,25
Enclosure Type	Anodized Aluminum	
Mounting	Din rail or panel mount	Note: All dimension
LEDs	Power LED, Ethernet link/data LED, & Ethernet speed LED	are ninches
<b>GATEWAY FEATURES &amp; FUNC</b>	CTIONS	
Alarming	Set <, <=, >, >=, ==, !=, and change-of-state rules on any data moving through the gateway. If alarm rule is triggered an email notification can be sent.	Din Rail
Gateway Security	You can configure up to 9 different users access to diagnostic and configuration screens.	Panel Mount
Translation Table	Allows for data manipulation during protocol translation. Scaling and other data format changes can occur in the gateway.	••••
Status and Counters	Protocol specific status, counters, and error messages are accessible within the gateway's diagnostics page. They can also be delivered to a connected device.	NOT EXACTLY WHAT YOU WERE LOOKING FOR? Real Time Automation offers a full line of gateway products. Give us a call at 1-800-249-1612. Or, check out a listing at <a href="https://www.rtautomation.com/products">www.rtautomation.com/products</a> . We also offer customizations for unique applications.
Diagnostic Logging Page	Allows users to see and log start up sequences, protocol specific messages & error messages.	

CATALOG #	DESCRIPTION
460MRSBC-N700	Connects a Modbus RTU master with as many as 32 BACnet/IP
	servers



Made in the

U.S.A.



Always In





