CONTACT US!

1-800-249-1612 rtautomation.com

Real Time Automation Gateways

460MRSBC-NNA4

Modbus RTU to BACnet/IP

FEATURES

- Fully configurable Modbus RTU slave
- Move up to 100 groups of 512 contiguous coils or 512 contiguous registers to or from your Modbus RTU master
- Fully configurable BACnet/IP client
- BACnet/IP supports device, binary I/O/V, analog I/O/V, multistate I/O/V, and character string value object types
- Effortless Browser
 Based Configuration,
 no programming
 software is required
- Simple data translation allows you to manipulate data as it passes between protocols
- Guaranteed Stock
- 5-Year Hardware Warranty

Connect BACnet/IP Servers to a Modbus RTU Master

The 460MRSBC moves data between a Modbus RTU master device and up to 32 BACnet/IP server devices.

The 460MRSBC module bundles your BACnet/IP data and makes it available as Modbus RTU data. The module provides complete Modbus RTU slave and BACnet/IP client capability.

How Do I Use the 460MRSBC-NNA4 in My Application?

To your Modbus RTU master device, the gateway acts as a Modbus RTU slave. To your BACnet/IP server devices, the gateway acts as a BACnet/IP client.

You can both send data to your BACnet/IP server devices and read current status data. Up to 1200 analog and 1600 binary objects can be mapped into or out of up to 512 contiguous registers and coils in the Modbus RTU master.

Why Use Real Time Automation as a Gateway Supplier?

While there are certainly other companies offering protocol gateways, there is no one who provides the level of support and service that you receive from RTA.


When you call, a live person answers the phone. When you talk with sales, you will get honest answers and recommendations. When you get support, it is from an engineer who had a hand in the product's development, and support doesn't require a ticket or 24-hour wait.



A Solution, A Philosophy, the RTA Way. We understand the long hours spent on a factory floor and the pressure to keep a line running and product flowing. That's how Real Time Automation came to be. You want easy-to-use solutions where the hardest part is to open the box. You need customer support second to none. If you get all that and a fun customer experience all the better. Thirty years later, our mission remains the same: To move your data where you need it, when you need it, and how you need it.

| Modbus RTU Slave | | |
|---|--|--|
| Operation Mode | Modbus RTU Slave | |
| Function Codes Supported | 1,2,3,4,5,6, 15 & 16 | |
| Swapping | Byte and Word Swapping | |
| Maximum Modbus RTU Master Connections | 1 | |
| Contiguous Data Areas | 200 Total - 100 reads & 100 writes | |
| Data Area Limits | 512 Contiguous Coils or 512 Contiguous Registers | |
| BACnet/IP Client | | |
| Operation Mode | BACnet/IP Client | |
| Supported Object Types | Device, BI/BO/BV, AI/AO/AV, MI/MO/MV, Character String Value | |
| Supported Service Codes | Read Property-A, Read Property Multiple-A, Write Property-A, Write Property Multiple-A, Device Dynamic Binding-A | |
| Maximum Connections | 32 | |
| Number Read/Write Scan Lines per Device | 200 Total - 100 reads & 100 writes | |
| Scan Line Support | Up to 128 Objects | |
| INCLUDED WITH GATEWAY | | |
| 3' power cable with flying leads | 5-year hardware warranty | |
| IPSetup software – automatically locates RTA gateway on the network | Unlimited firmware feature upgrades for life | |
| CAT5 crossover cable for direct connection to PC during programming | Complete, unlimited access to our industry leading support staff | |
| Manual | | |

| ELECTRICAL / ENVIRONMENTAL | | |
|---------------------------------------|---|--|
| DC Input Voltage | 12-24 VDC | |
| Maximum Baud Rate | 115K baud | DIN Rail Mount |
| Operating Temperature | -40 C to 85 C | |
| Certification | RoHS-Compliant, UL, CUL, CE Approvals | - |
| ENCLOSURE / HARDWARE | | , |
| Size | 3.88" x 2.57" x 1.06" | |
| Weight | 5.5 oz | |
| Enclosure Type | Anodized Aluminum | |
| Mounting | Din rail or panel mount | 2.57 |
| LEDs | Power LED & 2 general purpose LEDs on side | |
| GATEWAY FEATURES & FUNCTIO | GATEWAY FEATURES & FUNCTIONS | |
| Alarming | Set <, <=, >, >=, ==, !=, and change-of-state rules on any data moving through the gateway. If alarm rule is triggered an email notification can be sent. | N |
| Gateway Security | You can configure up to 9 different users access to diagnostic and configuration screens. | |
| Translation Table | Allows for data manipulation during protocol translation. Scaling and other data format changes can occur in the gateway. | 1.06 |
| Status and Counters | Protocol specific status, counters, and error messages are accessible within the gateway's diagnostics page. They can also be delivered to a connected device. | NOT EXACT Real Time Auto Give us a call a www.rtau custo |
| Diagnostic Logging Page | Allows users to see and log start up sequences, protocol specific messages & error messages. | |



NOT EXACTLY WHAT YOU WERE LOOKING FOR?

Real Time Automation offers a full line of gateway products. Give us a call at 1-800-249-1612. Or, check out a listing at www.rtautomation.com/products. We also offer customizations for unique applications.

| CATALOG # | DESCRIPTION |
|---------------|---|
| 460MRSBC-NNA4 | Connects a Modbus RTU master with as many as 32 BACnet/IP |
| | servers |



Made in the

U.S.A.



Always In







