## CONTACT US!

1-800-249-1612 rtautomation.com

## **Real Time Automation Gateways**

## 460MRSSC-NNA4

#### **Modbus Master to Siemens S7 PLC**

#### **FEATURES**

- Fully configurable Modbus RTU slave
- Move up to 100 groups of 512 contiguous coils or 512 contiguous registers to or from your Modbus RTU master
- Supports connections to five Siemens S7 PLCs
- Up to 150 read and 150 write requests per connection
- Effortless Browser
   Based Configuration,
   no programming
   software is required
- Simple data translation allows you to manipulate data as it passes between protocols
- Guaranteed Stock
- 5-Year Hardware Warranty

# **Get Your Modbus RTU Master Connected Directly to the Data Table of Your Siemens S7 PLC**

The 460MRSSC connects a Modbus RTU master device with up to five Siemens S7 PLCs.

Best of all, the product is made in the USA, always in stock, and comes with 5-year warranty.

#### How Do I Use the 460MRSSC-NNA4 in My Application?

You allocate two memory blocks in your Siemens S7 PLC. One area is a user-defined set of output addresses sending data to your Modbus RTU master. The other is input only data receiving data from your Modbus RTU master.

It's really that simple. Need to modify your data as it passes from one protocol to the other? No problem. Each data mapping you apply can be modified with up to three mathematic functions. Add 4 to a value, multiply by 4 and divide by 10 with ease.

### Why Use Real Time Automation as a Gateway Supplier?

While there are certainly other companies offering protocol gateways, there is no one who provides the level of support and service that you receive from RTA.

When you call, a live person answers the phone. When you talk with sales, you will get honest answers and recommendations. When you get support, it is from an engineer who had a hand in the product's development, and support doesn't require a ticket or 24-hour wait.



A Solution, A Philosophy, the RTA Way. We understand the long hours spent on a factory floor and the pressure to keep a line running and product flowing. That's how Real Time Automation came to be. You want easy-to-use solutions where the hardest part is to open the box. You need customer support second to none. If you get all that and a fun customer experience all the better. Thirty years later, our mission remains the same: To move your data where you need it, when you need it, and how you need it.

Modbus RTU Slave	
Operation Mode	Modbus RTU Slave
Function Codes Supported	1,2,3,4,5,6, 15 & 16
Swapping	Byte and Word Swapping
Maximum Modbus RTU Master Connections	1
Contiguous Data Areas	200 Total - 100 reads & 100 writes
Data Area Limits	512 Contiguous Coils or 512 Contiguous Registers
S7 Client	
PLC Support	S7 300/400/1200/1500
Maximum Number of PLCs Supported	5
Maximum Number of Inputs/Outputs per PLC	150
Maximum Number of Bytes per Scan Line	400
Memory Area Access	Input (I), Output (Q), and Data Block( DB)
Supported Data Types	8 Bit Int, 16 Bit Int, 32 Bit Int, 32 Bit Float, Bool and Char Array
INCLUDED WITH GATEWAY	
3' power cable with flying leads	5-year hardware warranty
IPSetup software – automatically locates RTA gateway on the network	Unlimited firmware feature upgrades for life
CAT5 crossover cable for direct connection to PC during programming	Complete, unlimited access to our industry leading support staff
Manual	

<b>ELECTRICAL / ENVIRONMENTA</b>	L	
DC Input Voltage	12-24 VDC	
Maximum Baud Rate	115K baud	Di
Operating Temperature	-40 C to 85 C	
Certification	RoHS-Compliant, UL, CUL, CE Approvals	
ENCLOSURE / HARDWARE		
Size	3.88" x 2.57" x 1.06"	
Weight	5.5 oz	
Enclosure Type	Anodized Aluminum	
Mounting	Din rail or panel mount	
LEDs	Power LED & 2 general purpose LEDs on side	
<b>GATEWAY FEATURES &amp; FUNC</b>	TIONS	
	Set <, <=, >, >=, ==, !=, and change-of-state rules	
Alarming	on any data moving through the gateway. If alarm	
3	rule is triggered an email notification can be sent.	
	You can configure up to 9 different users access to	
Gateway Security	diagnostic and configuration screens.	
	alagnostis and somigaration corosino.	
	Allows for data manipulation during protocol	
Translation Table	translation. Scaling and other data format changes	
	can occur in the gateway.	
		NoT
	Protocol specific status, counters, and error	NOT
Status and Counters	messages are accessible within the gateway's	Real Ti
Status and Counters	diagnostics page. They can also be delivered to a	Give u
	connected device.	7
	Allows users to see and log start up sequences,	
Diagnostic Logging Page	protocol specific messages & error messages.	
	protocol specific messages & error messages.	

	•	3.88
2.57	Note: All dimensions are in Inches	
		00000
1.06	000 F	

#### NOT EXACTLY WHAT YOU WERE LOOKING FOR?

Real Time Automation offers a full line of gateway products. Give us a call at 1-800-249-1612. Or, check out a listing at <a href="https://www.rtautomation.com/products">www.rtautomation.com/products</a>. We also offer customizations for unique applications.

CATALOG #	DESCRIPTION
460MRSSC-NNA4	Connects up to five Siemens S7 PLCs with a Modbus RTU master



Made in the

U.S.A.



Always In







