

460MS-NNA1

Interconnect Modbus TCP Clients

FEATURES

- Fully configurable Modbus TCP/IP server
- Move up to 100 groups of 512 contiguous coils or 512 contiguous registers to or from your Modbus TCP/IP client

Connect Up to 10 Modbus TCP Clients

The 460MS can handle up to 10 Modbus TCP connections at one time.

Best of all, the product is made in the USA, always in stock, and comes with a five-year warranty.

How Do I Use the 460MS-NNA1 in My Application?


The 460MS also allows for data manipulation when mapping. You can scale or adjust your data before it reaches your Modbus client.

It really is that simple.

Why Use Real Time Automation as a Gateway Supplier?

While there are certainly other companies offering protocol gateways, there is no one who provides the level of support and service that you receive from RTA.

When you call, a live person answers the phone. When you talk with sales, you will get honest answers and recommendations. When you get support, it is from an engineer who had a hand in the product's development, and support doesn't require a ticket or 24-hour wait.



TCP/IP Client 460MS-NNA1 TCP/IP Client

A Solution, A Philosophy, the RTA Way. We understand the long hours spent on a factory floor and the pressure to keep a line running and product flowing. That's how Real Time Automation came to be. You want easy-to-use solutions where the hardest part is to open the box. You need customer support second to none. If you get all that and a fun customer experience all the better. Thirty years later, our mission remains the same: To move your data where you need it, when you need it, and how you need it.

Modbus TCP Server	
Operation Mode	Modbus TCP/IP Server
Function Codes Supported	1,2,3,4,5,6, 15 & 16
Swapping	Byte and Word Swapping
Maximum Modbus TCP/IP Client Connections	10
Contiguous Data Areas	200 Total - 100 reads & 100 writes
Data Area Limits	512 Contiguous Coils or 512 Contiguous Registers

ELECTRICAL / ENVIRONMENTAL		
DC Input Voltage	12-24 VDC	
Maximum Baud Rate	115K baud	DIN Rail Mount
Operating Temperature	-40 C to 85 C	
Certification	RoHS-Compliant, UL, CUL, CE Approvals	3.88 —
ENCLOSURE / HARDWARE		,
Size	3.88" x 2.57" x 1.06"	
Weight	5.5 oz	
Enclosure Type	Anodized Aluminum	
Mounting	Din rail or panel mount	2.57
LEDs	Power LED & 2 general purpose LEDs on side	
INCLUDED WITH GATEWAY		Note: All dimensions
3' Power Cable with Flying leads	Manual	are in Inches
Complete, Unlimited Access to our Industry Leading Support Staff.	5 Year Hardware Warranty	1.06
IPSetup software – Automatically locates RTA Gateway on the network	Unlimited Firmware Feature Upgrades for Life	
CAT5 Cross over cable for direct connection to PC during programming		NOT EXACTLY WHAT YOU WERE LOOKING FOR? Real Time Automation offers a full line of gateway products Give us a call at 1-800-249-1612. Or, check out a listing a www.rtautomation.com/products. We also offer customizations for unique applications.

CATALOG #	DESCRIPTION
460MS-NNA1	Connects up to 10 Modbus TCP clients



Made in the

U.S.A.



Always In Stock





