

CONTACT US! 1-800-249-1612 rtautomation.com

### **Real Time Automation Gateways**

## 460MSSC-NNA1

### Wireless Modbus TCP/IP to Siemens S7 PLC

### FEATURES

- Fully configurable Modbus TCP/IP server
- Move up to 100 groups of 512 contiguous coils or 512 contiguous registers to or from your Modbus TCP/IP client
- Supports connections to five Siemens S7 PLCs
- Up to 150 read and 150 write requests per connection
- Effortless Browser Based Configuration, no programming software is required
- Simple data translation allows you to manipulate data as it passes between protocols
- Guaranteed Stock
- 5-Year Hardware Warranty

# Get Your Modbus TCP/IP Client Connected Directly to the Data Table of Your Siemens S7 PLC over Wi-Fi

The 460MSSC connects a Modbus TCP/IP client device and up to five Siemens S7 PLCs.

Best of all, the product is made in the USA, always in stock, and comes with 5-year warranty.

### How Do I Use the 460MSSC-NNA1 in My Application?


You allocate two memory blocks in your Siemens S7 PLC. One area is a userdefined set of output addresses sending data to your Modbus TCP/IP client. The other is input only data receiving data from your Modbus TCP/IP client.

It's really that simple. Need to modify your data as it passes from one protocol to the other? No problem. Each data mapping you apply can be modified.

#### Why Use Real Time Automation as a Gateway Supplier?

While there are certainly other companies offering protocol gateways, there is no one who provides the level of support and service that you receive from RTA.

When you call, a live person answers the phone. When you talk with sales, you will get honest answers and recommendations. When you get support, it is from an engineer who had a hand in the product's development, and support doesn't require a ticket or 24-hour wait.



A Solution, A Philosophy, the RTA Way. We understand the long hours spent on a factory floor and the pressure to keep a line running and product flowing. That's how Real Time Automation came to be. You want easy-to-use solutions where the hardest part is to open the box. You need customer support second to none. If you get all that and a fun customer experience all the better. Thirty years later, our mission remains the same: To move your data where you need it, when you need it, and how you need it.


## **Specification**

| Modbus TCP Server   |  |
|---|--|
| Operation Mode  | Modbus TCP/IP Server   |
| Function Codes Supported  | 1,2,3,4,5,6, 15 & 16   |
| Swapping  | Byte and Word Swapping   |
| Maximum Modbus TCP/IP Client Connections                            | 10   |
| Contiguous Data Areas   | 200 Total - 100 reads & 100 writes                                   |
| Data Area Limits  | 512 Contiguous Coils or 512 Contiguous Registers                     |
| S7 Client   |  |
| PLC Support   | S7 300/400/1200/1500   |
| Maximum Number of PLCs Supported                                    | 5  |
| Maximum Number of Inputs/Outputs per PLC                            | 150  |
| Maximum Number of Bytes per Scan Line                               | 400  |
| Memory Area Access  | Input (I), Output (Q), and Data Block( DB)                           |
| Supported Data Types  | 8 Bit Int, 16 Bit Int, 32 Bit Int, 32 Bit Float, Bool and Char Array |
| INCLUDED WITH GATEWAY   |  |
| 3' power cable with flying leads                                    | 5-year hardware warranty   |
| IPSetup software – automatically locates RTA gateway on the network | Unlimited firmware feature upgrades for life                         |
| CAT5 crossover cable for direct connection to PC during programming | Complete, unlimited access to our industry leading support staff     |
| Manual  |  |

| ELECTRICAL / ENVIRONMENTAL            |   |   |
|---------------------------------------|---|---|
| DC Input Voltage                      | 12-24 VDC   |   |
| Maximum Baud Rate                     | 115K baud   | DIN Rail Mount  |
| Operating Temperature                 | -40 C to 85 C   |   |
| Certification                         | RoHS-Compliant, UL, CUL, CE Approvals   |   |
| ENCLOSURE / HARDWARE                  |   | ,   |
| Size                                  | 3.88" x 2.57" x 1.06"   |   |
| Weight                                | 5.5 oz  |   |
| Enclosure Type                        | Anodized Aluminum   |   |
| Mounting                              | Din rail or panel mount   | 2.57  |
| LEDs                                  | Power LED & 2 general purpose LEDs on side  |   |
| <b>GATEWAY FEATURES &amp; FUNCTIO</b> | NS  |   |
| Alarming                              | Set <, <=, >, >=, ==, !=, and change-of-state rules<br>on any data moving through the gateway. If alarm<br>rule is triggered an email notification can be sent. | Note: All dimensions<br>are in Inches   |
| Gateway Security                      | You can configure up to 9 different users access to<br>diagnostic and configuration screens.  |   |
| Translation Table                     | Allows for data manipulation during protocol translation. Scaling and other data format changes can occur in the gateway.                                       |   |
| Status and Counters                   | Protocol specific status, counters, and error messages are accessible within the gateway's diagnostics page. They can also be delivered to a connected device.  | NOT EXACTLY WHAT YOU WERE LOOKING FOR?<br>Real Time Automation offers a full line of gateway products.<br>Give us a call at 1-800-249-1612. Or, check out a listing at<br>www.rtautomation.com/products. We also offer<br>customizations for unique applications. |
| Diagnostic Logging Page               | Allows users to see and log start up sequences, protocol specific messages & error messages.  |   |

| CATALOG #    | DESCRIPTION  |
|--------------|--|
| 460MSSC-NNA1 | Connects up to five Siemens S7 PLCs with a Modbus TCP client over wireless |





Always In Stock





**Real Time Automation, Inc.** 

solutions@rtautomation.com

1-800-249-1612