

CONTACT US! 1-800-249-1612 rtautomation.com

460PSUS-N2E

PROFINET IO Controller to OPC UA

FEATURES

- Fully configurable
 PROFINET device
- Supports up to 1280 bytes of data in each direction on PROFINET IO
- Fully configurable OPC UA server
- Up to 10 read and write groups with up to 200 nodes per group
- Effortless Browser Based Configuration, no programming software is required
- Simple data translation allows you to manipulate data as it passes between protocols
- Guaranteed Stock
- 5-Year Hardware Warranty

Connect a PROFINET PLC to OPC UA

The 460PSUS moves data between a PROFINET controller device up to three OPC UA clients.

Best of all, the product is made in the USA, always in stock, and comes with 5-year warranty.

How Do I Use the 460PSUS-N2E in My Application?

Data from up to 12 PROFINET slots is mapped to mapped to OPC nodes. The data moves bidirectionally.

It's really that simple to convert data to the information systems you need to monitor your application.

Why Use Real Time Automation as a Gateway Supplier?

While there are certainly other companies offering protocol gateways, there is no one who provides the level of support and service that you receive from RTA.

When you call, a live person answers the phone. When you talk with sales, you will get honest answers and recommendations. When you get support, it is from an engineer who had a hand in the product's development, and support doesn't require a ticket or 24-hour wait.



A Solution, A Philosophy, the RTA Way. We understand the long hours spent on a factory floor and the pressure to keep a line running and product flowing. That's how Real Time Automation came to be. You want easy-to-use solutions where the hardest part is to open the box. You need customer support second to none. If you get all that and a fun customer experience all the better. Thirty years later, our mission remains the same: To move your data where you need it, when you need it, and how you need it.

Specification

Profinet IO Server	
Maximum Number of Slots	10 Slots in, 10 Slots out
Slot Data Segment Sizes	8, 16, 32, 64 or 128 Bytes
Each Slot Can be Defined for a Single Data Type of	Int8, int16, int32, int64, UInt8, Uint16, Uint32, Uint64, float, double, binary8, binary16 or binary32, Short String
Total Data Supported in Each Direction	1280 Bytes
Maximum Profinet IO Controller Connections	1
String Support	1 string per slot
OPC UA Client	
Operation Mode	OPC UA Server
Simultaneous Connections Supported	3
Max number of Input Nodes per Node Type	200
Max number of Output Nodes per Node Type	200
Array Support	Boolean,64 Bit Integer, 64 Bit Unsigned Int and 64 bit Float
Profiles Supported	UA 1.03 Micro Embedded Server and Data Access
INCLUDED WITH GATEWAY	
3' power cable with flying leads	5-year hardware warranty
IPSetup software – automatically locates RTA gateway on the network	Unlimited firmware feature upgrades for life
CAT5 crossover cable for direct connection to PC during programming	Complete, unlimited access to our industry leading support staff
Manual	

DC Input Voltage 12-24 VDC 115K baud Maximum Baud Rate Operating Temperature -40 C to 85 C RoHS-Compliant, UL, CUL, CE Approvals, Class Certification I Div 2 **ENCLOSURE / HARDWARE** 5.40" x 3.83" x 1.19" Size Weight 7.6 oz Enclosure Type Anodized Aluminum Mounting Din rail or panel mount Power LED & 2 general purpose LEDs on side LEDs **GATEWAY FEATURES & FUNCTIONS** Set <, <=, >, >=, ==, !=, and change-of-state rules Alarming on any data moving through the gateway. If alarm rule is triggered an email notification can be sent. You can configure up to 9 different users access to Gateway Security diagnostic and configuration screens.

ELECTRICAL / ENVIRONMENTAL

Translation TableAllows for data manipulation during protocol
translation. Scaling and other data format changes
can occur in the gateway.Status and CountersProtocol specific status, counters, and error
messages are accessible within the gateway's
diagnostics page. They can also be delivered to a
connected device.Diagnostic Logging PageAllows users to see and log start up sequences,
protocol specific messages are accessible within the sequences,
econnected device.


NOT EXACTLY WHAT YOU WERE LOOKING FOR? Real Time Automation offers a full line of gateway products. Give us a call at 1-800-249-1612. Or, check out a listing at www.rtautomation.com/products. We also offer customizations for unique applications.

CATALOG #	DESCRIPTION
460PSUS-N2E	Connect a PROFINET Controller to OPC UA

protocol specific messages & error messages.



Made in the



Always In Stock





Real Time Automation, Inc.

solutions@rtautomation.com

1-800-249-1612