

460QT-NNA1

Connect Generic MQTT Brokers to AWS or Azure

FEATURES

- Bring your factory data to the cloud
- Support for MQTT, AWS and Azure

Connect up to Four MQTT Brokers to AWS or Azure

The 460QT allows you connect multiple in-house MQTT brokers to AWS or Azure. Perfect for bridging OT based MQTT brokers to cloud-based applications.

Best of all, the product is made in the USA, always in stock, and comes with a 5-year warranty.

How Do I Use the 460QT-NNA1 in My Application?


Use data manipulation to modify your data as you transfer it between devices. The manipulation fields allow up to three operations.

It really is that simple.

Why Use Real Time Automation as a Gateway Supplier?

While there are certainly other companies offering protocol gateways, there is no one who provides the level of support and service that you receive from RTA.

When you call, a live person answers the phone. When you talk with sales, you will get honest answers and recommendations. When you get support, it is from an engineer who had a hand in the product's development, and support doesn't require a ticket or 24-hour wait.



A Solution, A Philosophy, the RTA Way. We understand the long hours spent on a factory floor and the pressure to keep a line running and product flowing. That's how Real Time Automation came to be. You want easy-to-use solutions where the hardest part is to open the box. You need customer support second to none. If you get all that and a fun customer experience all the better. Thirty years later, our mission remains the same: To move your data where you need it, when you need it, and how you need it.


rtautomation.com

Specification


MQTT	
Operation Mode	Generic MQTT, Amazon Web Services (AWS), Microsoft Azure
Max Broker Connections	Up to 3 Generic MQTT Connections, 1 AWS, 1 Azure
Max Data Points Per Connection	1000 Read and 1000 Write Topics
Security	SSL certificate based cloud access
Supported Data Formats	JSON
Data Payload	Topic Name and Value

ELECTRICAL / ENVIRONMENTAL

DC Input Voltage	12-24 VDC	
Maximum Baud Rate	115K baud	
Operating Temperature	-40 C to 85 C	
Certification	RoHS-Compliant, UL, CUL, CE Approvals	
ENCLOSURE / HARDWARE		
Size	3.88" x 2.57" x 1.06"	
Weight	5.5 oz	
Enclosure Type	Anodized Aluminum	
Mounting	Din rail or panel mount	
LEDs	Power LED & 2 general purpose LEDs on side	
INCLUDED WITH GATEWAY		
3' Power Cable with Flying leads	Manual	
Complete, Unlimited Access to our Industry Leading Support Staff.	5 Year Hardware Warranty	
IPSetup software – Automatically locates RTA Gateway on the network	Unlimited Firmware Feature Upgrades for Life	
CAT5 Cross over cable for direct connection to PC during programming		



NOT EXACTLY WHAT YOU WERE LOOKING FOR? Real Time Automation offers a full line of gateway products. Give us a call at 1-800-249-1612. Or, check out a listing at www.rtautomation.com/products. We also offer customizations for unique applications.



Real Time Automation, Inc.

solutions@rtautomation.com

1-800-249-1612