

CONTACT US! 1-800-249-1612 rtautomation.com

460WISC-N2EW

Web Interface for Siemens S7 PLCs

FEATURES

- Get PLC data table entries encoded in either JSON or XML
- Bidirectional data transfer supports both HTTP GET and POST
- Supports connections to five Siemens S7 PLCs
- Up to 150 read and 150 write requests per connection
- Effortless Browser Based Configuration, no programming software is required
- Simple data translation allows you to manipulate data as it passes between protocols
- Guaranteed Stock
- 5-Year Hardware Warranty

Access Your Siemens S7 PLC Data via a Web Interface

The 460WISC moves data between up to five Siemens S7 PLCs via Web Services. The gateway presents the S7 data as JSON or XML files transferred via HTTP commands.

With the 460WISC, you are making a direct connection between XML/JSON data and the data table of your Siemens S7 PLC.

How Do I Use the 460WISC-N2EW in My Application?

Incoming and outgoing ASCII data is mapped to and from memory table addresses in your Siemens S7 PLC. One area is output being mapped as XML or JSON to your applications. The other is input blocks receiving data from your application.

It's really that simple.

Why Use Real Time Automation as a Gateway Supplier?

While there are certainly other companies offering protocol gateways, there is no one who provides the level of support and service that you receive from RTA.

When you call, a live person answers the phone. When you talk with sales, you will get honest answers and recommendations. When you get support, it is from an engineer who had a hand in the product's development, and support doesn't require a ticket or 24-hour wait.




A Solution, A Philosophy, the RTA Way. We understand the long hours spent on a factory floor and the pressure to keep a line running and product flowing. That's how Real Time Automation came to be. You want easy-to-use solutions where the hardest part is to open the box. You need customer support second to none. If you get all that and a fun customer experience all the better. Thirty years later, our mission remains the same: To move your data where you need it, when you need it, and how you need it.

Specification

| Web Interface | |
|---|---|
| Max Web Interface Connections | One (gateway acting as client) / Unlimited (gateway acting as server) |
| Encodings | JSON and XML |
| Proxy Support | HTTP, SOCKS5 for Client |
| Maximum Number of Input Data Points | 1000 JSON Fields or 1000 XML Tags |
| Maximum Number of Output Data Points | 1000 JSON Fields or 1000 XML Tags |
| HTTP Services | Client: POST only; Server: GET and POST |
| S7 Client | |
| PLC Support | S7 300/400/1200/1500 |
| Maximum Number of PLCs Supported | 5 |
| Maximum Number of Inputs/Outputs per PLC | 150 |
| Maximum Number of Bytes per Scan Line | 400 |
| Memory Area Access | Input (I), Output (Q), and Data Block(DB) |
| Supported Data Types | 8 Bit Int, 16 Bit Int, 32 Bit Int, 32 Bit Float, Bool and Char Array |
| INCLUDED WITH GATEWAY | |
| 3' power cable with flying leads | 5-year hardware warranty |
| IPSetup software – automatically locates RTA gateway on the network | Unlimited firmware feature upgrades for life |
| CAT5 crossover cable for direct connection to PC during programming | Complete, unlimited access to our industry leading support staff |
| Manual | |

| ELECTRICAL / ENVIRONMENTAL | | |
|--|---|---|
| DC Input Voltage | 12-24 VDC | |
| Maximum Baud Rate | 115K baud | f |
| Operating Temperature | -40 C to 85 C | |
| Certification | RoHS-Compliant, UL, CUL, CE Approvals, Class I Div 2 | |
| ENCLOSURE / HARDWARE | | |
| Size | 5.40" x 3.83" x 1.19" | |
| Weight | 7.6 oz | |
| Enclosure Type | Anodized Aluminum | |
| Mounting | Din rail or panel mount | |
| LEDs | Power LED & 2 general purpose LEDs on side | |
| GATEWAY FEATURES & FUNCTION | NS | |
| Alarming | Set <, <=, >, >=, ==, !=, and change-of-state rules on any data moving through the gateway. If alarm rule is triggered an email notification can be sent. | • |
| Gateway Security | You can configure up to 9 different users access to diagnostic and configuration screens. | |
| Translation Table | Allows for data manipulation during protocol translation. Scaling and other data format changes can occur in the gateway. | [|
| Status and Counters | Protocol specific status, counters, and error messages are accessible within the gateway's diagnostics page. They can also be delivered to a connected device. | NOT EXACT Real Time Auto Give us a call a <u>www.rtau</u> custo |
| Diagnostic Logging Page | Allows users to see and log start up sequences, protocol specific messages & error messages. | |



TLY WHAT YOU WERE LOOKING FOR? tomation offers a full line of gateway products. at 1-800-249-1612. Or, check out a listing at automation.com/products. We also offer tomizations for unique applications.

| CATALOG # | DESCRIPTION |
|--------------|--|
| 460WISC-N2EW | Connect up to five Siemens S7 PLCs via a web interface |



Made in the



Always In Stock





Real Time Automation, Inc.

solutions@rtautomation.com

1-800-249-1612