

CONTACT US! 1-800-249-1612 rtautomation.com

Real Time Automation Gateways

460WIUS-NNA1

Web Interface to OPC UA with Wi-Fi

FEATURES

- Get PLC data table entries encoded in either JSON or XML
- Bidirectional data transfer supports both HTTP GET and POST
- Fully configurable OPC UA server
- Up to 10 read and write groups with up to 200 nodes per group
- Effortless Browser Based Configuration, no programming software is required
- Simple data translation allows you to manipulate data as it passes between protocols
- Guaranteed Stock
- 5-Year Hardware Warranty

Add a RESTful Interface to Connect an OPC UA Controller Wirelessly

The 460WIUS moves data between up to three OPC UA clients and your web applications. Use that data to easily build a log, a dashboard, archive data or create a sophisticated alarm system. The 460WIUS delivers OPC UA data as a JSON or XML files via HTTP commands.

Best of all, the product is made in the USA, always in stock, and comes with 5-year warranty.

How Do I Use the 460WIUS-NNA1 in My Application?


OPC UA node data is mapped to an XML or JSON encoded file. These files are passed via HTTP commands.

It's really that simple to convert data to the information systems you need to monitor your application.

Why Use Real Time Automation as a Gateway Supplier?

While there are certainly other companies offering protocol gateways, there is no one who provides the level of support and service that you receive from RTA.

When you call, a live person answers the phone. When you talk with sales, you will get honest answers and recommendations. When you get support, it is from an engineer who had a hand in the product's development, and support doesn't require a ticket or 24-hour wait.



A Solution, A Philosophy, the RTA Way. We understand the long hours spent on a factory floor and the pressure to keep a line running and product flowing. That's how Real Time Automation came to be. You want easy-to-use solutions where the hardest part is to open the box. You need customer support second to none. If you get all that and a fun customer experience all the better. Thirty years later, our mission remains the same: To move your data where you need it, when you need it, and how you need it.

Specification


Web Interface		
Max Web Interface Connections	One (gateway acting as client) / Unlimited (gateway acting as server)	
Encodings	JSON and XML	
Proxy Support	HTTP, SOCKS5 for Client	
Maximum Number of Input Data Points	1000 JSON Fields or 1000 XML Tags	
Maximum Number of Output Data Points	1000 JSON Fields or 1000 XML Tags	
HTTP Services	Client: POST only; Server: GET and POST	
OPC UA Client		
Operation Mode	OPC UA Server	
Simultaneous Connections Supported	3	
Max number of Input Nodes per Node Type	200	
Max number of Output Nodes per Node Type	200	
Array Support	Boolean,64 Bit Integer, 64 Bit Unsigned Int and 64 bit Float	
Profiles Supported	Supported UA 1.03 Micro Embedded Server and Data Access	
INCLUDED WITH GATEWAY		
3' power cable with flying leads	5-year hardware warranty	
IPSetup software – automatically locates RTA gateway on the network	Unlimited firmware feature upgrades for life	
CAT5 crossover cable for direct connection to PC during programming	Complete, unlimited access to our industry leading support staff	
Manual		

ELECTRICAL / ENVIRONMENTA	L	
DC Input Voltage	12-24 VDC	
Maximum Baud Rate	115K baud	DIN Rail Mount
Operating Temperature	-40 C to 85 C	
Certification	RoHS-Compliant, UL, CUL, CE Approvals	· 3.88
ENCLOSURE / HARDWARE		
Size	3.88" x 2.57" x 1.06"	
Weight	5.5 oz	
Enclosure Type	Anodized Aluminum	
Mounting	Din rail or panel mount	2.57
LEDs	Power LED & 2 general purpose LEDs on side	
GATEWAY FEATURES & FUNCTIONS		
Alarming	Set <, <=, >, >=, ==, !=, and change-of-state rules on any data moving through the gateway. If alarm rule is triggered an email notification can be sent.	Note: All dimensions are in Inches
Gateway Security	You can configure up to 9 different users access to diagnostic and configuration screens.	
Translation Table	Allows for data manipulation during protocol translation. Scaling and other data format changes can occur in the gateway.	
Status and Counters	Protocol specific status, counters, and error messages are accessible within the gateway's diagnostics page. They can also be delivered to a connected device.	NOT EXACTLY WHAT YOU WERE LOOKING FOR? Real Time Automation offers a full line of gateway products. Give us a call at 1-800-249-1612. Or, check out a listing at www.rtautomation.com/products. We also offer customizations for unique applications.
Diagnostic Logging Page	Allows users to see and log start up sequences, protocol specific messages & error messages.	

CATALOG #	DESCRIPTION
460WIUS-NNA1	Connect up to three OPC clients via a web interface







Always In Stock





solutions@rtautomation.com

1-800-249-1612